

Lindy 2m DisplayPort 1.4 Cable, Cromo Line

Gamintojas: **LINDY** · Modelis: **36302** · EAN: **4002888363020** · Prekės kodas: **740413**



31,90 €

Kaina su PVM

Be PVM: **26,36 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Superior performance and design DisplayPort cable
- ✓ Supports UHD resolutions up to 8K 7680x4320@60Hz 4:2:2 8bit, including 4K 4096x2160@120Hz 4:4:4 8bit
- ✓ Chrome design ABS housing, 24K gold plated connectors and contacts
- ✓ Triple shielded cable, corrosion resistant, high performance tinned copper 28AWG conductors
- ✓ DisplayPort 1.4, 8K 4K, 3D, 32.4Gbps; 10 year warranty



Aprašymas

From the Lines cable connectivity concept developed by Lindy, Cromo Line DisplayPort cables are high performance, designer connections that combine premium construction materials with striking connector architecture.

Cromo Line DisplayPort Cables feature triple shielded construction with 28AWG conductors for premium performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 8K 7680x4320@60Hz 4:2:2 8bit, including 4K 4096x2160@120Hz 8bit, are supported. Cromo Line DisplayPort cables are capable of delivering 4:4:4 colour spacing for the most accurate colour representation possible.

Cromo Line cables feature sleek chrome design ABS housing to complement the aesthetics of style focused commercial and home applications.

Cromo Line DisplayPort cables are available in lengths from 0.5m to 5m.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Kabel und Adapter > Displayport Kabel und Adapter [+1987][-131]
Features	
Cable length	2 m
Connector 1	DisplayPort
Connector 2	DisplayPort
Connector 1 gender	Male
Connector 2 gender	Male
Maximum resolution	7680 x 4320 pixels
Product colour	Grey
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Gold
DisplayPort version	1.4
Supported graphics resolutions	7680 x 4320
Maximum refresh rate	60 Hz
Cable material	Tinned copper
Cable shielding	Copper
Jacket material	Polyvinyl chloride (PVC)
Connector housing material	Acrylonitrile butadiene styrene (ABS)
AWG wire size	28
Data transfer rate	32.4 Gbit/s
Contact material	Phosphor copper
Connector material	Gold
Colour sampling	4:2:2
Cable type	Round cable
Nominal attenuation	300kHz-825MHz 5dB,825MHz-2.475GHz 5dB,2.475GHz-4.125GHz 12dB,4.125GHz-5.1GHz 20dB
Operational conditions	
Operating temperature (T-T)	-20 - 80 °C
Storage temperature (T-T)	-25 - 85 °C
Certificates	

Certification	RoHS, REACH, UL,
Weight & dimensions	
Cable diameter	7.3 mm
Connector 1 dimensions (WxDxH)	19.7 x 12 x 38.9 mm
Connector 2 dimensions (WxDxH)	19.7 x 12 x 38.9 mm
Bend radius (min)	7.3 cm
Packaging data	
Package type	Polybag
Logistics data	
Harmonized System (HS) code	84733080
Matmenys ir svoris	
Svoris	0,14kg