

TP-Link Omada SG3452XMPP network switch Managed L2+ Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Black

Gamintojas: **TP-LINK** · Modelis: **SG3452XMPP** · EAN: **8885020620870** · Prekės kodas: **740807**



1 010,89 €

Kaina su PVM

Be PVM: **835,45 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4x 10 Gbps SFP+ slots
- ✓ 8x Gigabit 802.af/at/bt PoE++ ports (Max 90 W PoE budget for each port)
- ✓ 40x Gigabit 802.3af/at PoE+ ports (Max 30 W budget for each port)
- ✓ 750 W total PoE budget*
- ✓ Centralized cloud management via the web or the Omada app†
- ✓ Standalone management via web, CLI, SNMP, and RMON



Aprašymas

TP-LINK Omada SG3452XMPP V1.8 - Switch - L2+ - managed - 40 x 10/100/1000 (PoE+) (SG3452XMPP)

Techninė specifikacija

Specifications

Sandėlio grupė

> Netzwerk > Switches [+1607][-273]

Management features

Switch type	Managed
Switch layer	L2+
Quality of Service (QoS) support	Yes
Web-based management	Yes
Cloud-managed	Yes
ARP inspection	Yes
Configuring Location Settings (CLI)	Yes
System event log	Yes

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	48
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
SFP+ module slots quantity	4
Console port	RJ-45/Micro-USB
Power connector	AC-in jack

Network

Networking standards	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3z
10G support	Yes
Port mirroring	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Rate limiting	Yes
Spanning tree protocol	Yes
Head-of-line (HOL) blocking	Yes
VLAN support	Yes

Data transmission

MAC address table	16000 entries
Switching capacity	176 Gbit/s
Forwarding rate	130.9 Mpps
Store-and-forward	Yes
Jumbo frames support	Yes
Jumbo frames	9000
Packet buffer memory	12 MB

Security

DHCP features	DHCP client, DHCP relay, DHCP server
Access Control List (ACL)	Yes
IGMP snooping	Yes
MAC address filtering	Yes
Static port security	Yes
SSH/SSL support	Yes
BPDU filtering/protection	Yes
IP-MAC-Port binding	Yes
Authentication	Auto VLAN, Guest VLAN

Multicast features

Multicast support	Yes
-------------------	-----

Design

Rack mounting	Yes
Form factor	1U
Product colour	Black
Reset button	Yes
LED indicators	Yes
Number of fans	3 fan(s)

Power

Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (max)	635.7 W

Power over Ethernet (PoE)

Power over Ethernet (PoE)	Yes
Power over Ethernet plus (PoE+) ports quantity	40
Power over Ethernet 4PPoE (PoE++) ports quantity	8
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	750 W

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C

Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Heat dissipation	2169.2 BTU/h
Weight & dimensions	
Width	440 mm
Depth	330 mm
Height	44 mm
Packaging content	
Cables included	AC
Quick start guide	Yes
Certificates	
Certification	CE, FCC, RoHS
Matmenys ir svoris	
Matmenys (I × P × A)	10,00cm × 47,00cm × 53,00cm
Svoris	6,96kg