

TP-Link ES228GP network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Gamintojas: **TP-LINK** · Modelis: **ES228GP** · EAN: **1210002609760** · Prekės kodas: **741641**



264,91 €

Kaina su PVM

Be PVM: **218,93 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Managed L2 Web-based management
- ✓ Quality of Service (QoS) support
- ✓ Basic switching RJ-45 Ethernet ports quantity: 26
- ✓ MAC address table: 8000 entries Switching capacity: 56 Gbit/s
- ✓ Rack mounting
- ✓ AC Power over Ethernet (PoE)



Aprašymas

Omada Central Essentials — A Free and Easy Cloud-Based Network Management

Omada Central Essentials is a free, easy-to-use version of the Omada Central.

It provides cloud-based centralized management and monitoring for the Omada networking system, covering access points, switches, and gateways, ideal for surveillance networks and small businesses.

Multiple Application Scenarios

Surveillance

Works with IP Cameras

Wi-Fi Coverage

Works with Access Points

Wired Connections

Works with Non-PoE Devices such as PCs and Printers

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	26
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
SFP module slots quantity	2
Network	
Networking standards	IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3at
Port mirroring	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
VLAN support	Yes
Virtual LAN features	MTU VLAN, Port-based VLAN, Tagged VLAN
Data transmission	
MAC address table	8000 entries
Switching capacity	56 Gbit/s
Forwarding rate	41.67 Mpps
Store-and-forward	Yes
Number of queues	8
Jumbo frames support	Yes
Jumbo frames	15000

Packet buffer memory	4 MB
Security	
DHCP features	DHCP client
IGMP snooping	Yes
Loop protection	Yes
Queue scheduling algorithms	Weighted Round Robin (WRR)
Design	
Rack mounting	Yes
Product colour	Black
Number of fans	2 fan(s)
Power	
Power source	AC
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Input current	4 A
Power protection features	Surge protection
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	PoE+
Power over Ethernet (PoE) ports quantity	24
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	250 W
Operational conditions	
Operating temperature (T-T)	-5 - 45 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	440 mm
Depth	180 mm
Height	44 mm
Packaging content	
Cables included	AC
Manual	Yes

Certificates

Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
-------------------------	---

Matmenys ir svoris

Matmenys (I × P × A)	53,00cm × 28,00cm × 8,00cm
----------------------	----------------------------

Svoris	3,57kg
--------	--------