

## LevelOne 8-Port Fast Ethernet PoE Industrial Switch, 4 PoE Outputs, 802.3at/af PoE, 126W, -40°C to 75°C

Gamintojas: **LEVELONE** · Modelis: **IFP-0801** · EAN: **4015867196663** · Prekės kodas: **741936**



### 267,89 €

Kaina su PVM

Be PVM: **221,40 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

### Pagrindinės savybės

- ✓ Basic switching RJ-45 Ethernet ports quantity: 12
- ✓ 10BASE-T, 100BASE-TX
- ✓ MAC address table: 1000 entries Switching capacity: 1.6 Gbit/s
- ✓ Power over Ethernet (PoE)



### Aprašymas

The LevelOne IFP-0801 is 10/100M industrial 8 port high power POE switch is equipped with 4 port 30Watts PSE. It is designed for 48-56VDC input sources, especially for IP surveillance, traffic monitoring and for a broad range of applications. It can be used as a stand-alone device for buses, trucks, and other vehicles for Surveillance purposes. It is being rigorously tested for your Security, Transportation and Telco application.

- PoE ports can support the IEEE 802.3at standard and power up 30W devices
- 10/100Mbps, full/half-duplex, auto-negotiation, auto-MDI/MDIX
- -40°C to 75°C operating temperature range
- Provides DIN-rail, wall or desktop mounting
- IP30 metal case
- Redundant power inputs with Terminal Block and DC Jack

## Techninė specifikacija

| Specifications                                |                                                                  |
|-----------------------------------------------|------------------------------------------------------------------|
| Sandėlio grupė                                | > Netzwerk > Switches [+1607][-273]                              |
| Ports & interfaces                            |                                                                  |
| Basic switching RJ-45 Ethernet ports quantity | 12                                                               |
| Basic switching RJ-45 Ethernet ports type     | Fast Ethernet (10/100)                                           |
| Installed SFP modules quantity                | 0                                                                |
| Installed SFP+ modules quantity               | 0                                                                |
| Network                                       |                                                                  |
| Networking standards                          | IEEE 802.3, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x |
| 10G support                                   | No                                                               |
| Copper ethernet cabling technology            | 10BASE-T, 100BASE-TX                                             |
| Full duplex                                   | Yes                                                              |
| Flow control support                          | Yes                                                              |
| Auto MDI/MDI-X                                | Yes                                                              |
| Auto-negotiation                              | Yes                                                              |
| Data transmission                             |                                                                  |
| MAC address table                             | 1000 entries                                                     |
| Switching capacity                            | 1.6 Gbit/s                                                       |
| Store-and-forward                             | Yes                                                              |
| Packet buffer memory                          | 1 MB                                                             |
| Design                                        |                                                                  |
| Product colour                                | Black                                                            |
| LED indicators                                | Link, Power, Status                                              |
| Wall mountable                                | Yes                                                              |
| DIN rail mounting                             | Yes                                                              |
| Safety                                        | IEC EN60950-1                                                    |
| Performance                                   |                                                                  |
| Plug and Play                                 | Yes                                                              |
| Mean time between failures (MTBF)             | 510304 h                                                         |
| Power                                         |                                                                  |
| Redundant power supply (RPS) support          | Yes                                                              |
| Power consumption (typical)                   | 5.76 W                                                           |

**Power over Ethernet (PoE)**

|                                                |           |
|------------------------------------------------|-----------|
| Power over Ethernet (PoE)                      | Yes       |
| Power over Ethernet plus (PoE+) ports quantity | 4         |
| Power over Ethernet (PoE) voltage range        | 44 - 56 V |
| Power over Ethernet (PoE) power per port       | 30 W      |
| Total Power over Ethernet (PoE) budget         | 126 W     |

**Other features**

|                     |     |
|---------------------|-----|
| Terminal block port | Yes |
|---------------------|-----|

**Operational conditions**

|                                   |             |
|-----------------------------------|-------------|
| Operating temperature (T-T)       | -40 - 75 °C |
| Operating relative humidity (H-H) | 5 - 95%     |

**Weight & dimensions**

|        |         |
|--------|---------|
| Width  | 105 mm  |
| Depth  | 36.2 mm |
| Height | 142 mm  |
| Weight | 525 g   |

**Packaging content**

|        |     |
|--------|-----|
| Manual | Yes |
|--------|-----|

**Packaging data**

|                         |        |
|-------------------------|--------|
| Wall mounting kit       | Yes    |
| Terminal block included | Yes    |
| Package type            | Box    |
| DIN rail included       | Yes    |
| Package width           | 165 mm |
| Package depth           | 65 mm  |
| Package height          | 215 mm |
| Package weight          | 730 g  |

**Certificates**

|               |                                                                                                                                               |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Certification | EMI: FCC Part 15 Subpart B Class A CE EN 55022 Class A EMC: EN55022, EN55024<br>EN50155/EN60068-2-6 EN50155/EN60068-2-27 EN50155/EN60068-2-32 |
|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------|

**Logistics data**

|                            |        |
|----------------------------|--------|
| Country of origin          | Taiwan |
| Master (outer) case width  | 350 mm |
| Master (outer) case length | 240 mm |

|                            |        |
|----------------------------|--------|
| Master (outer) case height | 570 mm |
|----------------------------|--------|

|                             |          |
|-----------------------------|----------|
| Harmonized System (HS) code | 85176990 |
|-----------------------------|----------|

|                                  |         |
|----------------------------------|---------|
| Master (outer) case gross weight | 12.6 kg |
|----------------------------------|---------|

|                                  |          |
|----------------------------------|----------|
| Products per master (outer) case | 16 pc(s) |
|----------------------------------|----------|

#### Matmenys ir svoris

|        |        |
|--------|--------|
| Svoris | 0,73kg |
|--------|--------|