

Lindy 0.5m DisplayPort 1.4 Cable, Gold Line

Gamintojas: **LINDY** · Modelis: **36290** · EAN: **4002888362900** · Prekės kodas: **741939**



65,90 €

Kaina su PVM

Be PVM: **54,46 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ No compromise, ultimate performance DisplayPort cable for demanding environments and mission critical systems
- ✓ Supports UHD resolutions up to 8K 7680x4320@60Hz 4:2:2 8bit
- ✓ Full metal 24K gold plated housing, 24K gold plated connectors and contacts
- ✓ Low attenuation triple shielded cable, corrosion resistant, high performance OFC 24AWG conductors
- ✓ DisplayPort 1.4 compliant: 3D, 8K, 4K, 32.4Gbps, DisplayPort Certified; 25 year warranty



Aprašymas

From the Lines cable connectivity concept developed by Lindy, Gold Line DisplayPort cables are the no compromise, high performance connection solution for use in the most demanding professional environments.

Gold Line DisplayPort cables feature triple shielded construction with 24AWG OFC conductors for premium performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 8K 7680x4320@60Hz 4:2:2 8bit, including 4K 4096x2160@120Hz 4:4:4 8bit and HDCP are supported. DisplayPort 1.4 technology and DisplayPort compliance certification ensures compatibility with all DisplayPort enabled devices.

These superior quality cables utilise a unique low attenuation design that ensures consistent and reliable transmission even over very long

distances.

Gold DisplayPort cables are available in lengths from 0.5m to 20m.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Kabel und Adapter > Displayport Kabel und Adapter [+1987][[-131]
Features	
Cable length	0.5 m
Connector 1	DisplayPort
Connector 2	DisplayPort
Connector 1 gender	Male
Connector 2 gender	Male
Maximum resolution	4096 x 2160 pixels
Product colour	Gold, Grey
Connector contacts plating	Gold
Supported graphics resolutions	4096 x 2160
Jacket material	Polyvinyl chloride (PVC)
AWG wire size	24
Operational conditions	
Operating temperature (T-T)	-20 - 80 °C
Storage temperature (T-T)	25 - 80 °C
Logistics data	
Harmonized System (HS) code	84733080
Matmenys ir svoris	
Svoris	0,15kg