

Lindy 3m DisplayPort 1.2 Cable, Cromo Line

Gamintojas: **LINDY** · Modelis: **36303** · EAN: **4002888363037** · Prekės kodas: **741944**



43,90 €

Kaina su PVM

Be PVM: **36,28 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Superior performance and design DisplayPort cable
- ✓ Supports UHD resolutions up to 4K 4096x2160@60Hz 4:4:4 10bit
- ✓ Chrome design ABS housing, 24K gold plated connectors and contacts
- ✓ Triple shielded cable, corrosion resistant, high performance tinned copper 28AWG conductors
- ✓ DisplayPort 1.2, 4K, 3D, 21.6Gbps; 10 year warranty



Aprašymas

From the Lines cable connectivity concept developed by Lindy, Cromo Line DisplayPort cables are high performance, designer connections that combine premium construction materials with striking connector architecture.

Cromo Line DisplayPort Cables feature triple shielded construction with 28AWG conductors for premium performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 4K 4096x2160@60Hz 4:4:4 10bit, including stereoscopic 3D, are supported. Cromo Line DisplayPort cables are capable of delivering 4:4:4 colour spacing for the most accurate colour representation possible.

Cromo Line cables feature sleek chrome design ABS housing to complement the aesthetics of style focused commercial and home applications.

Cromo Line DisplayPort cables are available in lengths from 0.5m to 5m.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Kabel und Adapter > Displayport Kabel und Adapter [+1987][-131]
Features	
Cable length	3 m
Connector 1	DisplayPort
Connector 2	DisplayPort
Connector 1 gender	Male
Connector 2 gender	Male
Maximum resolution	4096 x 2160 pixels
Product colour	Chrome, Grey
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Gold
DisplayPort version	1.2
Supported video modes	2160p
Maximum refresh rate	60 Hz
3D	Yes
Cable material	Tinned copper
Cable shielding	Copper
Jacket material	Polyvinyl chloride (PVC)
Connector housing material	Acrylonitrile butadiene styrene (ABS)
AWG wire size	28
Data transfer rate	21.6 Gbit/s
Contact material	Phosphor bronze
Connector material	Gold
Colour sampling	4:4:4
Cable type	Round cable
Nominal attenuation	300kHz-825MHz 5dB, 825MHz-2.475GHz 5dB, 2.475GHz-4.125GHz 12dB, 4.125GHz-5.1GHz 20dB
Operational conditions	
Operating temperature (T-T)	-20 - 80 °C
Storage temperature (T-T)	-25 - 85 °C

Certificates

Compliance certificates	REACH, RoHS
Certification	RoHS, REACH, UL

Weight & dimensions

Cable diameter	7.3 mm
Connector 1 dimensions (WxDxH)	19.7 x 12 x 38.9 mm
Connector 2 dimensions (WxDxH)	19.7 x 12 x 38.9 mm
Bend radius (min)	7.3 cm

Packaging data

Package type	Polybag
--------------	---------

Packaging content

Manual	Yes
--------	-----

Logistics data

Pallet net height	3.89 cm
Harmonized System (HS) code	84733080

Supplier features

Product or Article Information Sheet available?	Yes
---	-----

Matmenys ir svoris

Svoris	0,24kg
--------	--------