

LevelOne 26-Port Fast Ethernet PoE Switch, 24 PoE Outputs, 2 x Gigabit RJ45, 150W

Gamintojas: **LEVELONE** · Modelis: **FGP-2601W150** · EAN: **4015867202791** · Prekės kodas: **741951**



513,90 €

Kaina su PVM

Be PVM: **424,71 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ IEEE 802.3af/at PoE compliant to simplify deployment and installation
- ✓ Power protection: overvoltage / overcurrent / overtemperature
- ✓ IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- ✓ PoE on/off control per port by dip switches
- ✓ 19-inch metal housing
- ✓ 24 Fast Ethernet PoE ports and 2 Gigabit ports



Aprašymas

The LevelOne FGP-2601 series are unmanaged PoE switches with 24 RJ45 PoE ports. The switches are IEEE 802.3af/at compliant, providing power and data over a single Ethernet cable to any PoE device, with a total power budget of 150/250/380/500/630W, or up to 30W per port. Ideal for desktops, they are also 19-inch rack-mountable, which provides convenient and flexible installation. The FGP-2601 switches are designed for small-to-medium businesses that require an affordable solution for deploying PoE infrastructure.

Techninė specifikacija

Specifications

Sandėlio grupė

> Netzwerk > Switches [+1607][-273]

Management features

Switch typeUnmanaged

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	26
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Fast Ethernet (copper) ports quantity	24
Gigabit Ethernet (copper) ports quantity	2
Power connector	AC-in jack

Network

Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Cable types supported	Cat3, Cat4, Cat5, Cat5e, Cat6, Cat7
Full duplex	Yes
Flow control support	Yes

Data transmission

MAC address table	4000 entries
Switching capacity	8.8 Gbit/s
Jumbo frames support	Yes
Jumbo frames	10000
Packet forwarding rate (1 Gbps)	1488000 pps
Packet forwarding rate (100 Mbps)	148800 pps
Packet forwarding rate (10 Mbps)	14880 pps
Packet buffer memory	0.512 MB

Design

Rack mounting	Yes
Product colour	Black
Housing material	Metal
LED indicators	LAN, PoE, Power, Uplink
On/off switch	Yes

Performance

Mean time between failures (MTBF)	50000 h
Power	
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power protection features	Over current, Over voltage, Overheating
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet plus (PoE+) ports quantity	24
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	150 W
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width	200 mm
Depth	44 mm
Height	440 mm
Weight	2.9 kg
Packaging content	
Cables included	AC
Manual	Yes
Packaging data	
Package width	260 mm
Package depth	95 mm
Package height	540 mm
Package weight	3.5 kg
Certificates	
Certification	FCC Class A, CE
Logistics data	
Country of origin	Taiwan
Master (outer) case width	510 mm
Master (outer) case length	280 mm

Master (outer) case height	555 mm
Harmonized System (HS) code	85176990
Master (outer) case gross weight	18 kg
Matmenys ir svoris	
Svoris	3,39kg