

LevelOne FEU-0812 network switch Unmanaged Fast Ethernet (10/100) Black

Gamintojas: **LEVELONE** · Modelis: **FEU-0812** · EAN: **4015867226667** · Prekės kodas: **742048**



21,90 €

Kaina su PVM

Be PVM: **18,10 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Provides flexibility of 8 x 10/100BASE-TX ports
- ✓ 10/100Mbps, full/half-duplex, auto-negotiation, auto-MDI/MDIX
- ✓ Quick and easy installation
- ✓ Supports 1K MAC address auto-learning and auto-aging
- ✓ Simple Plug and Play installation



Aprašymas

The LevelOne FEU-0812 is a wire-speed, non-blocking networking device that provides 8 ports 10/100 Mbps Ethernet connections. All ports support auto-negotiation and auto-MDI/MDIX sensing, eliminating the need for crossover cables or Uplink Ports. Each port can be used as general network port or as connecting port into a router, server, hub or another network switch.

Techninė specifikacija

Specifications

Sandėlio grupė

> Netzwerk > Switches [+1607][-273]

Management features

Switch type	Unmanaged
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Fast Ethernet (10/100)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Power connector	DC-in jack
Network	
Networking standards	IEEE 802.3, IEEE 802.3az, IEEE 802.3u, IEEE 802.3z
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-T
Full duplex	Yes
Half duplex	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Data transmission	
MAC address table	1000 entries
Packet buffer memory	1.19 MB
Design	
Rack mounting	No
Stackable	No
Product colour	Black
LED indicators	Activity, Link, Power
Performance	
Plug and Play	Yes
Fanless	Yes
Power	
Power source	DC
Power supply included	Yes
DC input voltage	5 V
Input current	0.55 A
Power consumption (typical)	1.7 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No

Operational conditions

Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions

Width	130.7 mm
Depth	52.3 mm
Height	20 mm
Weight	110 g

Packaging data

AC adapter included	Yes
Package type	Box
Package width	145 mm
Package depth	80 mm
Package height	80 mm
Package weight	214 g

Certificates

Certification	CE RoHS
---------------	---------

Logistics data

Country of origin	China
Harmonized System (HS) code	85176990

Matmenys ir svoris

Svoris	0,21kg
--------	--------