

AVer PTZ330UV2 8 MP White 3840 x 2160 pixels 60 fps Exmor 25.4 / 2.8 mm (1 / 2.8")

Gamintojas: **AVERMEDIA** · Modelis: **61S3320000AH** · EAN: **4719552127696** · Prekės kodas: **742135**



2 482,90 €

Kaina su PVM

Be PVM: **2 051,98 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4K Ultra HD Resolution
- ✓ 30X Optical Zoom
- ✓ IP/HDMI/USB/3G-SDI
- ✓ Human Detection AI
- ✓ Presenter Mode
- ✓ Zone Mode
- ✓ Hybrid Mode
- ✓ Intuitive Web UI
- ✓ Upside-Down Installation
- ✓ Voice Tracking



Aprašymas

AI Auto Tracking PTZ Camera

The PTC330UV2 AI Auto Tracking PTZ Camera makes powerful and reliable Pro AV capability available to everyone. Drawing inspiration from the AVer Professional PTZ Camera family, the PTC330UV2 features in-house AI functions like Presenter Mode, Zone Mode and Hybrid Mode auto tracking, thanks to Human Detection processing. Combine the 30X Optical Zoom lens and 4K resolution with hybrid auto tracking and smooth PTZ functions for broadcasting, streaming, or recording. Your exciting journey of audio and video capturing starts here!

Upgrade Your Cameras to NDI®!

Upgrade your AVer cameras with NDI®|HX. A separate NDI®|HX license key is required for each camera, and internet connection is required for

initial activation.

4K Output Resolution

Equipped with 4K resolution, the PTC330UV2 provides ultra-precise auto tracking. The PTC330UV2 also features a Sony sensor that maintains a truly impressive video performance through every frame of your production.

30X Optical Zoom & 12X Digital Zoom

The zoom power of the PTC330UV2 camera reaches an incredible 360X (30X optical and 12X digital zoom). It works even while the camera is panning and tilting, allowing you to highlight content and rapidly change shooting angles. Operate a closer and clearer video feed with the unbeatable PTZ performance of the PTC330UV2.

Human Detection AI

Welcome AVer’s most advanced AI tool yet—Human Detection. This highly accurate processing function enables PTC330UV2 to easily detect and capture human forms and moving objects in seconds. Never miss a tracking target again.

Click & Track

With the PTC310HWV2, you can simply click on a target to quickly adjust the shooting angle and initiate precise tracking, ensuring you can redirect in an instant. This advanced feature is easy for anyone to operate via both remote control and intuitive Web UI.

Presenter Mode

Track your target everywhere with Presenter Mode. This feature gives presenters the flexibility to leave the stage and interact with the audience, all while being continuously tracked. The camera stays locked on its target, even if other people or objects get in the way.

Zone Mode

Zone Mode enhances your ability to capture content on multiple displays. Create up to four Content Zones to steadily capture the content on display rather than the presenter’s movements.

Hybrid Mode

Hybrid Mode provides the utmost freedom of movement for performing artists. Use preset areas for segment tracking to have the camera automatically snap to a full view of each preset location as the artist moves between it. If the artist leaves the preset areas, the camera seamlessly transitions to tracking mode and follows the artist wherever they go.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Netzwerkkamera und Zubehör [+1996][-361]
Camera	
Megapixel (approx.)	8 MP
Camera type	Single camera
Sensor type	Exmor
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")
Zoom capability	Yes
Optical zoom	30x
Digital zoom	1x
Combined zoom	30x

Focal length range	4.5 - 135 mm
Field of view (wide)	69.2°
Field of view (tele)	2.8°
Horizontal field of view (wide)	62.3°
Horizontal field of view (tele)	2.5°
Vertical field of view (wide)	37.3°
Vertical field of view (tele)	1.4°
Minimum illumination	0.46 lx
Progressive scan	Yes
Flip & mirror	Yes
White balance	ATW, Auto, Manual, One push
Focus adjustment	Auto/Manual
Wide Dynamic Range (WDR)	Yes
Back Light Compensation (BLC)	Yes
Number of camera presets	10
Gain control type	Auto/Manual
PTZ control	Yes
PTZ protocols	Pelco-P/D, VISCA
3D NR (Noise Reduction)	Yes
Snapshot	Yes
Face tracking	Yes
Photo feature	Yes
Video	
Maximum video resolution	3840 x 2160 pixels
Maximum frame rate	60 fps
HD type	4K Ultra HD
Supported video modes	720p, 1080p, 2160p
Video formats supported	M-JPEG, YUY2
Number of TV lines	1400
Design	
Product colour	White
Mounting type	Stand/Wall mounting
Image stabilizer	Yes
Tilt angle range	-30 - 90°
Pan range	-170 - 170°

Tally light	Yes
Web-based management	Yes
Tilt speed (min)	0.1 °/sec
Tilt speed (max)	100 °/sec
Tilt preset speed	200 °/sec
Pan speed (min)	0.1 °/sec
Pan speed (max)	100 °/sec
Pan preset speed	200 °/sec
Cable management	Yes
Country of origin	Taiwan

Ports & interfaces

HDMI ports quantity	1
USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity	1
RS-232 ports	1
RS-422 ports	1
Ethernet LAN (RJ-45) ports	1
DC-in jack	Yes
3G-SDI output	Yes
Line-in	Yes

Power

Power source type	DC
AC input frequency	50/60 Hz
AC input voltage	100-240 V
DC input voltage	12 V
Input current	2 A
Power consumption (typical)	19 W

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	20 - 95%

Packaging content

Power supply included	Yes
Remote control included	Yes

Cables included	RS-232
Warranty card	Yes
Screws included	Yes
Number of screws	8
Mounting kit	Yes
AC adapter included	Yes
Cable ties included	Yes
Number of cable ties	4
Mounting brackets included	Yes
System requirements	
Windows operating systems supported	Yes
Mac operating systems supported	Yes
Other operating systems supported	iOS
Performance	
Screen mirroring	Yes
Auto framing	Yes
Auto-tracking	Yes
Remote control function	Yes
Remote control type	IR
Cable lock slot	Yes
Cable lock slot type	Kensington
Audio	
Audio channels	2
Audio codecs	AAC-LC
Technical details	
Warranty period	2 year(s)
Network	
Ethernet LAN data rates	10,100,1000 Mbit/s
Streaming capability	Yes
Network streaming	Yes
Multi-stream capability	5: HDMI / RTSP / NDI HX2 / USB(4Kp60) & 3G-SDI(1080P60) or 4: HDMI / RTSP / NDI HX3(4Kp60) & 3G-SDI(1080P60)
Bit rate control	Constant Bit Rate (CBR), Variable Bit Rate (VBR)
Bit rate range	512 - 12000 Kbit/s
Network configuration	DHCP, IP Address Gateway, Subnet Mask, DNS

Supported network protocols	IPv4, TCP, UDP, ARP, ICMP, IGMP, HTTP, HTTPS, DHCP, RTP / RTCP, RTSP, RTMP, SRT, HLS, NDI, LLDP, VISCA over IP
-----------------------------	--

Logistics data

Products per master (outer) case	1 pc(s)
Products per pallet	72 pc(s)
Harmonized System (HS) code	8525890000

Weight & dimensions

Width	180 mm
Depth	145 mm
Height	192 mm
Weight	2 kg

Packaging data

Package width	292 mm
Package depth	245 mm
Package height	303 mm
Package weight	4.9 kg
Package type	Box

Matmenys ir svoris

Svoris	2,00kg
--------	--------