

ACT DisplayPort to MTP/MPO adapter set to extend a DisplayPort connection up to 8K@60Hz (AK4165)

Gamintojas: **ACT** · Modelis: **AK4165** · EAN: **8716065539288** · Prekės kodas: **742155**



345,90 €

Kaina su PVM

Be PVM: **285,87 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Extend an 8K DisplayPort connection up to 300 meters (OM4)
- ✓ Suited for use with MTP/MPO OM3/OM4 fiber cable with polarity B
- ✓ Max. resolution: 8K@60Hz / bandwidth 32.4Gbps / HDCP 2.3/HDR/4:4:4/CEC/EDID support
- ✓ Aluminium housing / gold-plated connectors / Kevlar protected fiber / LSZH cable jacket
- ✓ Including MTP/MPO couplers female - female
- ✓ TX and RX are easily exchangeable
- ✓ RX is USB powered



Aprašymas

Extend an 8K DisplayPort signal over a distance up to 300 meters with the AK4165 DisplayPort to MTP/MPO adapter set. The adapter set is suited for use with OM3/OM4 MTP/MPO cables with polarity B. The transmitter (TX) and receiver (RX) units are easily exchangeable. Take advantage of the benefits of fiber optics.

Advantage of fiber optic

With an OM3/OM4 MTP/MPO cable the optimal signal, bandwidth and speed are maintained over the entire length of max. 300 meters (with OM4, max. 100m with OM3). The data and video is sent via fiber and is therefore not affected by Electromagnetic Interference or Radio

Frequency Interference.

Flexible TX and RX placement

The transceiver (TX) and the receiver (RX) are easily exchangeable. Instead of a standard uni-directional cable, the TX and RX can be used bidirectionally by only swapping the source and display cable ends instead of the complete cable.

Also available

Besides the DisplayPort MTP/MPO adapters, an HDMI adapter set is available as well.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Kabel und Adapter > Displayport Kabel und Adapter [+1987][131]
Features	
Connector 1	DisplayPort
Connector 2	DisplayPort
Connector 1 gender	Male
Connector 2 gender	Male
Maximum resolution	7680 x 4320 pixels
Product colour	Pink
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Copper
DisplayPort version	1.4
Supported graphics resolutions	4096 x 2160, 7680 x 4320
HDCP	Yes
Jacket material	Polyvinyl chloride (PVC)
Data transfer rate	32.4 Gbit/s
Bandwidth	32400 MB/s
Certificates	
Compliance certificates	CE, UKCA
Certification	CE, ANSI/TIA-568.2-D
Weight & dimensions	
Cable diameter	3 mm
Matmenys ir svoris	
Svoris	1,00kg