Dahua Technology WizSense NVR4104-EI 1U White

Gamintojas: **DAHUA** · Modelis: **DHI-NVR4104-EI** · EAN: **6923172584151** · Prekės kodas: **742167**

234,90 €

Kaina su PVM

Be PVM: **194,13 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format
- ✓ Access, storage or forwarding at 80 Mbps
- ✓ Max. decoding capability: 16 × 1080p@30 fps. Supports adaptive decoding
- ✓ AI by NVR: 1-channel face detection and recognition; 2-channel perimeter protection; up to 10 face databases and 20,000 face images; 4-channel SMD Plus
- ✓ AI by Camera: Face detection and recognition, perimeter protection; SMD Plus; people counting; stereo analysis; heat map
- ✓ Connected to the third-party network cameras
- ✓ Security baseline 2.3

Aprašymas

Dahua Lite series NVR is easy to install, cost effective and compatible with a wide variety of third-party devices, providing a great solution for small and medium surveillance systems. It is ideal for home safety, supermarkets, warehouses, educational institutions, and financial institutions.

Functions
- Face Recognition
Dahua Face Recognition technology extracts the features of captured faces and compares them with that in face database.
- **Perimeter Protection**
Automatically filters out false alarms caused by animals, rustling leaves, bright lights, etc. Enables system to act secondary recognition for the

targets. Improves alarm accuracy.

- **SMD Plus**

With intelligent algorithm, Dahua Smart Motion Detection technology can categorize the targets that trigger motion detection and filter the motion detection alarm triggered by non-concerned targets to realize effective and accurate alarm.

- **AI Search**

With AI search, operators can search for videos by the attributes of targets and event types, which helps them to quickly and efficiently investigate where and when targets appeared and events took place.

- **Heat Map by Camera**

Dahua heat map technology is used to display the crowd density and people appearance probability. Export and display the crowd status by different colors. Generally, the crowd status is the statistics of people quantity in space and time dimensions.

- **ANPR by Camera**

With deep learning algorithm, Dahua ANPR technology can recognize the number plate information of vehicles in the image with ANPR cameras. Support blocklist/allowlist mode, searching target vehicles from recorded video.

- **Quick Pick**

Dahua Quick Pick technology can enable users to quickly pick up the human/vehicle targets that they are interested in, which facilitates retrieval from SMD events.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Netzwerkkamera und Zubehör [+1996][-361]
Performance	
Video input channels	4 channels
Maximum resolution	3840 x 2160 pixels
Video recording modes	720p, 960p, 1080p
Supported resolutions	1 HDMI, 1 VGA HDMI: 3840 × 2160, 1920 × 1080, 1280 × 1024, 1280 × 720 VGA: 1920 × 1080, 1280 × 1024, 1280 × 720 *Simultaneous/heterogeneous video sources output for VGA and HDMI is configurable
People counting	Yes
Multi-screen	Yes
Audio formats supported	G.711 A-law, G.711 µ-law, G.726, PCM
Video formats supported	H.264, H.264+, H.265, H.265+
Image formats supported	MJPEG
Operating system installed	Embedded LINUX
Backup function	Yes
Input bandwidth	80 Mbit/s
Output bandwidth	80 Mbit/s
Face detection	Yes
Wireless LAN features	
Wi-Fi	No
Hard drive	

Maximum storage capacity	16 TB
HDD interface	SATA
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	10,100 Mbit/s
HDMI output	Yes
HDMI ports quantity	1
VGA (D-Sub) output ports	1
USB 2.0 ports quantity	2
Audio RCA inputs	1
Audio RCA outputs	1
Supported network protocols	HTTP; HTTPS; TCP/IP; IPv4/IPv6; UPnP; SNMP; UDP; SMTP; NTP; DHCP; DNS; IP Filter; PPPoE; DDNS; FTP; Alarm Server; IP Search (Support Dahua IP camera; DVR; NVS; etc.); P2P; auto register
Features	
Rack mounting	Yes
Rack capacity	1U
Product colour	White
Certification	FCC: 47 CFR FCC Part15, SubpartB, Class A CE-EMC: EN 55032:2015+A1:2020; EN IEC 61000-3-2:2019+A1:2021; EN 61000-3-3:2013+A1:2019+A2:2021; EN 55035:2017+A11:2020; EN 50130-4:2011+A1:2014 CE-LVD: EN 62368-1:2014
Power	
Power consumption (typical)	10 W
Output current	2 A
Output voltage	12 V
System requirements	
Mobile operating systems supported	Android, iOS
Browser supported	Chrome; IE9 and later; Firefox
Operational conditions	
Operating temperature (T-T)	-10 - 55 °C
Operating relative humidity (H-H)	10 - 93%
Storage temperature (T-T)	-20 - 60 °C
Weight & dimensions	
Width	204.6 mm
Depth	206.4 mm
Height	45.6 mm

Weight	450 g
Package width	364 mm
Package depth	96 mm
Package height	261 mm
Package weight	1.07 kg
Matmenys ir svoris	
Svoris	1,00kg