

LevelOne 16-Port Fast Ethernet PoE Switch, 802.3at/af PoE, 150W

Gamintojas: **LEVELONE** · Modelis: **FEP-1612W150** · EAN: **4015867199886** · Prekės kodas: **742527**



513,90 €

Kaina su PVM

Be PVM: **424,71 €**

Sandėlyje



Prekė internetu

Nuskuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Basic switching RJ-45 Ethernet ports quantity: 16
- ✓ Cat3, Cat4, Cat5 10BASE-T, 100BASE-TX
- ✓ MAC address table: 4000 entries Switching capacity: 3.2 Gbit/s
- ✓ Power over Ethernet (PoE)



Aprašymas

LevelOne FEP-1612 features 16 10/100Mbps Fast Ethernet ports with IEEE 802.3at/af PoE interfaces. It supports MDI / MDI-X convertible on 16 10/100Mbps ports and provides PoE inject function on PoE ports which are able to IEEE 802.3af or 802.3at compliant powered devices remotely.

The FEP-1612 equipped with the MDI/MDI-X auto detection for easily plug and play connection, regardless of cabling types in straight through or crossover. It also provides a simple, cost-effective, and highly reliable network connection for data and power transmission. Furthermore, it is the ideal device for bridging among Ethernet, Fast Ethernet workgroups and networks. It fits all kind of Ethernet installations such as campus, workgroup, department, enterprise, telecom or industrial applications.

The FEP-1612 features non-blocking 3.2Gbps backplane that greatly simplifies the tasks of upgrading your LAN for catering to increase bandwidth demands.

Key Features

- IEEE 802.3af/at PoE compliant to simplify deployment and installation
- Auto-detection and protection of non-standard PoE devices

- Supports 4K MAC address auto-learning and auto-aging
- 10/100Mbps, full/half-duplex, auto-negotiation, auto-MDI/MDIX
- 19-inch metal housing
- IEEE 802.3x Flow Control protects against lost packets for reliable data transmission

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	16
Basic switching RJ-45 Ethernet ports type	Fast Ethernet (10/100)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Network	
Networking standards	IEEE 802.3, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX
Cable types supported	Cat3, Cat4, Cat5
Full duplex	Yes
Flow control support	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Data transmission	
MAC address table	4000 entries
Switching capacity	3.2 Gbit/s
Store-and-forward	Yes
Packet forwarding rate (100 Mbps)	148000 pps
Packet forwarding rate (10 Mbps)	14880 pps
Design	
Product colour	Grey
Housing material	Metal
LED indicators	Activity, PoE, Power
Performance	
Buffer size	160 KB
Plug and Play	Yes

Power

AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Input current	5 A
Power consumption (typical)	150 W
Power protection features	Over current

Power over Ethernet (PoE)

Power over Ethernet (PoE)	Yes
Power over Ethernet plus (PoE+) ports quantity	16
Power over Ethernet (PoE) power per port	30 W

Operational conditions

Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-40 - 75 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	200 mm
Depth	480 mm
Height	44 mm
Weight	2.85 kg

Packaging content

Cables included	AC
Quick start guide	Yes

Packaging data

Package type	Box
Rubber feet	Yes
Package width	250 mm
Package depth	535 mm
Package height	90 mm
Package weight	3.7 kg

Certificates

Certification	CE, FCC
---------------	---------

Logistics data

Country of origin	Taiwan
-------------------	--------

Master (outer) case width	520 mm
Master (outer) case length	560 mm
Master (outer) case height	280 mm
Harmonized System (HS) code	85176990
Master (outer) case gross weight	19.8 kg
Products per master (outer) case	5 pc(s)
Matmenys ir svoris	
Svoris	3,19kg