

# LevelOne HUBBLE Fixed Dome IP Network Camera, H.265, 3-Megapixel, 802.3af PoE, IR LEDs, Indoor/Outdoor, Vandalproof

Gamintojas: **LEVELONE** · Modelis: **FCS-3306** · EAN: **4015867202739** · Prekės kodas: **742539**



## 479,90 €

Kaina su PVM

Be PVM: **396,61 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ 3-Megapixel high-definition resolution
- ✓ Video compression: H.264, H.265
- ✓ Built-in infrared LEDs for night viewing up to 30m
- ✓ Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- ✓ Vandal-proof IK10-rated housing
- ✓ Weatherproof IP68-rated housing



## Aprašymas

The LevelOne FCS-3306 Fixed Dome Outdoor Camera offers a highly reliable, cost-effective outdoor IP surveillance solution in a low-profile dome mounted casing, which is rated at IP68 and able to withstand outdoor operating conditions such as rain, snow, extreme heat, dust and humidity. The FCS-3306 offers 3-Megapixel resolution, and with 802.3af standard PoE, can use a single Cat.5 cable to run both power and data, making deployments easy and flexible. The dome mounting prevents malicious tampering with the camera, making it a secure and smart choice for all outdoor installations.

## Techninė specifikacija

### Specifications

Sandėlio grupė

&gt; Netzwerk &gt; Netzwerkkamera und Zubehör [+1996][-361]

**Performance**

|                              |                    |
|------------------------------|--------------------|
| Type                         | IP security camera |
| Placement supported          | Indoor & outdoor   |
| Connectivity technology      | Wired              |
| Wide Dynamic Range (WDR)     | Yes                |
| Day/night mode               | Yes                |
| Infrared (IR) cut-off filter | Yes                |
| Certification                | CF/FCC/UL          |

**Design**

|                                    |              |
|------------------------------------|--------------|
| Mounting type                      | Ceiling/wall |
| Product colour                     | White        |
| Form factor                        | Dome         |
| LED indicators                     | Power        |
| Protection features                | Vandal proof |
| International Protection (IP) code | IP68         |
| IK code                            | IK10         |
| Country of origin                  | Taiwan       |

**Camera**

|                           |              |
|---------------------------|--------------|
| Field of view (FOV) angle | 129°         |
| Camera shutter speed      | 1 - 100000 s |

**Image sensor**

|                     |                          |
|---------------------|--------------------------|
| Optical sensor size | 25.4 / 2.8 mm (1 / 2.8") |
|---------------------|--------------------------|

**Lens system**

|                         |        |
|-------------------------|--------|
| Number of lenses        | 1      |
| Maximum aperture number | 1.8    |
| Fixed focal length      | 2.1 mm |

**Night vision**

|                       |      |
|-----------------------|------|
| Night vision          | Yes  |
| Night vision distance | 30 m |
| LED type              | IR   |

**Video**

|                    |                    |
|--------------------|--------------------|
| Maximum resolution | 2048 x 1536 pixels |
| Total megapixels   | 3 MP               |

|                                               |                                                                                                                                                 |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Video formats supported                       | Raw                                                                                                                                             |
| Video compression formats                     | H.264, H.265, M-JPEG                                                                                                                            |
| Supported graphics resolutions                | 320 x 240, 640 x 480 (VGA), 800 x 600 (SVGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2048 x 1536 (QXGA)                        |
| Frame rate                                    | 30 fps                                                                                                                                          |
| <b>Network</b>                                |                                                                                                                                                 |
| Ethernet LAN                                  | Yes                                                                                                                                             |
| Wi-Fi                                         | No                                                                                                                                              |
| Bluetooth                                     | No                                                                                                                                              |
| Ethernet interface type                       | Fast Ethernet                                                                                                                                   |
| Networking standards                          | IEEE 802.3af                                                                                                                                    |
| Supported network protocols                   | IPv4/v6, TCP, UDP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, NTP, RTP, RTSP, RTCP, SMTP, FTP, IGMP, ICMP, ARP, Bonjour, UPnP, QoS, SNMP, IEEE 802.1X |
| Number of users                               | 16 user(s)                                                                                                                                      |
| Quality of Service (QoS) support              | Yes                                                                                                                                             |
| <b>Storage</b>                                |                                                                                                                                                 |
| Built-in HDD                                  | No                                                                                                                                              |
| Card reader integrated                        | Yes                                                                                                                                             |
| Compatible memory cards                       | MicroSDHC, MicroSDXC                                                                                                                            |
| <b>Ports &amp; interfaces</b>                 |                                                                                                                                                 |
| Ethernet LAN (RJ-45) ports                    | 1                                                                                                                                               |
| DC-in jack                                    | Yes                                                                                                                                             |
| Interface                                     | RJ-45                                                                                                                                           |
| <b>Security</b>                               |                                                                                                                                                 |
| Password protection                           | Yes                                                                                                                                             |
| Password protection type                      | User                                                                                                                                            |
| IP address filtering                          | Yes                                                                                                                                             |
| HTTPS encryption                              | Yes                                                                                                                                             |
| Alert notification type                       | E-mail                                                                                                                                          |
| <b>Management features</b>                    |                                                                                                                                                 |
| Reset button                                  | Yes                                                                                                                                             |
| <b>Power</b>                                  |                                                                                                                                                 |
| Power source type                             | PoE                                                                                                                                             |
| Power consumption (Power over Ethernet (PoE)) | 12.95 W                                                                                                                                         |
| DC output voltage                             | 12                                                                                                                                              |

|                           |     |
|---------------------------|-----|
| Power over Ethernet (PoE) | Yes |
|---------------------------|-----|

#### Operational conditions

|                             |             |
|-----------------------------|-------------|
| Operating temperature (T-T) | -40 - 60 °C |
|-----------------------------|-------------|

|                                   |         |
|-----------------------------------|---------|
| Operating relative humidity (H-H) | 0 - 80% |
|-----------------------------------|---------|

#### Weight & dimensions

|       |        |
|-------|--------|
| Width | 115 mm |
|-------|--------|

|       |        |
|-------|--------|
| Depth | 115 mm |
|-------|--------|

|        |       |
|--------|-------|
| Height | 87 mm |
|--------|-------|

|          |         |
|----------|---------|
| Diameter | 11.5 cm |
|----------|---------|

|        |       |
|--------|-------|
| Weight | 835 g |
|--------|-------|

#### Packaging data

|               |        |
|---------------|--------|
| Package width | 143 mm |
|---------------|--------|

|               |        |
|---------------|--------|
| Package depth | 132 mm |
|---------------|--------|

|                |        |
|----------------|--------|
| Package height | 173 mm |
|----------------|--------|

|                |       |
|----------------|-------|
| Package weight | 835 g |
|----------------|-------|

|              |     |
|--------------|-----|
| Package type | Box |
|--------------|-----|

#### Packaging content

|                   |   |
|-------------------|---|
| Number of cameras | 1 |
|-------------------|---|

|                 |     |
|-----------------|-----|
| Screws included | Yes |
|-----------------|-----|

|             |     |
|-------------|-----|
| Resource CD | Yes |
|-------------|-----|

#### Logistics data

|                             |          |
|-----------------------------|----------|
| Harmonized System (HS) code | 85258900 |
|-----------------------------|----------|

|                           |        |
|---------------------------|--------|
| Master (outer) case width | 270 mm |
|---------------------------|--------|

|                            |        |
|----------------------------|--------|
| Master (outer) case length | 350 mm |
|----------------------------|--------|

|                            |        |
|----------------------------|--------|
| Master (outer) case height | 580 mm |
|----------------------------|--------|

|                                  |         |
|----------------------------------|---------|
| Master (outer) case gross weight | 15.6 kg |
|----------------------------------|---------|

|                                  |          |
|----------------------------------|----------|
| Products per master (outer) case | 16 pc(s) |
|----------------------------------|----------|

#### Matmenys ir svoris

|        |        |
|--------|--------|
| Svoris | 0,84kg |
|--------|--------|