

LevelOne GEP-1221 network switch Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Gamintojas: **LEVELONE** · Modelis: **GEP-1221** · EAN: **4015867227978** · Prekės kodas: **742781**



208,89 €

Kaina su PVM

Be PVM: **172,64 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 8 Gigabit PoE ports/ 2 Port Gigabit and 2 Gigabit SFP slots
- ✓ IEEE 802.3af/at PoE compliant to simplify deployment and installation
- ✓ IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- ✓ 1000Mbps full-duplex, 10/100Mbps full/half-duplex, auto-negotiation, auto-MDI/MDIX
- ✓ Built-in power supply



Aprašymas

The GEP-1221 switch provides 10 port 10/100/1000M ports with 2 port SFP. It is designed for easy installation and high performance in an environment where traffic is on the network and the number of users increases continuously. It consists of 8 PSE/PoE ports. That can solve the limitation of the power outlet location and offer the system designer a flexible solution to locate the network device everywhere. The device size is specifically designed for medium to large workgroups. The Switch can be installed where space is limited; moreover it provides smooth network migration and easy upgrade to network capacity. The PoE switch can be rack-mount on 19" cabinet.

Techninė specifikacija

Specifications

Sandėlio grupė > Netzwerk > Switches [+1607][-273]

Management features

Switch type Unmanaged

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	10
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP+ modules quantity	0
Gigabit Ethernet (copper) ports quantity	10
SFP module slots quantity	2

Network

Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support	No
Auto MDI/MDI-X	Yes
Ethernet LAN data rates	1000 Mbit/s
Auto-negotiation	Yes

Data transmission

MAC address table	4000 entries
Switching capacity	22 Gbit/s

Design

Rack mounting	Yes
Stackable	No
Product colour	Black
LED indicators	Yes

Performance

Internal memory	2 MB
Fanless	Yes

Power

Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
Power consumption (typical)	10 W

Power over Ethernet (PoE)

Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	150 W
Operational conditions	
Operating temperature (T-T)	5 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	250 mm
Depth	150 mm
Height	40 mm
Weight	1.4 kg
Packaging content	
Quick start guide	Yes
Logistics data	
Harmonized System (HS) code	85176990
Matmenys ir svoris	
Svoris	1,70kg