

LevelOne 8-Port Fast Ethernet Switch

Gamintojas: **LEVELONE** · Modelis: **FSW-0808TX** · EAN: **4015867109540** · Prekės kodas: **743172**



35,90 €

Kaina su PVM

Be PVM: **29,67 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Unmanaged
- ✓ Basic switching RJ-45 Ethernet ports quantity: 8
- ✓ 10BASE-T, 100BASE-TX
- ✓ MAC address table: 1024 entries Switching capacity: 1.6 Gbit/s



Aprašymas

The LevelOne FSW-0808 is a wire-speed, non-blocking networking device that provides 8 ports 10/100Mbps Ethernet connections. All ports support auto-negotiation and auto-MDI/MDIX sensing, eliminating the need for crossover cables or Uplink Ports. Each port can be used as general network port or as connecting port into a router, server, hub or another network switch.

Easy Configuration and Maintenance

The LevelOne FSW-0808TX does not require software configuration. Users can immediately use any features of this product simply by attaching the cables and turning on the power. For instant error detection, the switch is equipped with a full range of LEDs to help you monitor and troubleshoot problems on your network.

Compact Size Design

This switch is compact specially designed to fit on the desktop or in other space-limited locations. The FSW-0808TX provides an ideal solution for businesses that crave a reliable network to exchange large data files and multimedia information with bandwidth-starving workgroup, departments, and offices.

- Provides flexibility of 8 x 10/100BASE-TX ports
- 10/100Mbps-Full/Half-duplex, Auto-Negotiation, Auto-MDI/MDIX
- Supports 1K MAC address auto-learning and auto-aging
- IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- Magnetic base for easy placement
- Quick and easy installation

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Management features	
Switch type	Unmanaged
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Fast Ethernet (10/100)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Power connector	DC-in jack
Network	
Networking standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX
Full duplex	Yes
Flow control support	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Data transmission	
MAC address table	1024 entries
Switching capacity	1.6 Gbit/s
Store-and-forward	Yes
Packet forwarding rate (100 Mbps)	148000 pps
Packet forwarding rate (10 Mbps)	14880 pps
Design	
Rack mounting	No
Stackable	No
Product colour	Grey

LED indicators	Activity, Link, Power
Performance	
Buffer size	96 KB
Power	
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Output voltage	5 V
Output current	1 A
Power consumption (typical)	2.8 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 90%
Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width	125 mm
Depth	69 mm
Height	30 mm
Packaging content	
Quick start guide	Yes
Packaging data	
AC adapter included	Yes
Package width	75 mm
Package depth	130 mm
Package height	90 mm
Package weight	300 g
Certificates	
Certification	FCC, CE, RoHS
Logistics data	
Country of origin	China
Harmonized System (HS) code	85176990
Matmenys ir svoris	

Svoris

0,28kg