

LevelOne 5-Port Gigabit PoE Switch, 802.3at/af PoE, 4 PoE Outputs, 115W

Gamintojas: **LEVELONE** · Modelis: **GEP-0521** · EAN: **4015867185742** · Prekės kodas: **743274**



303,90 €

Kaina su PVM

Be PVM: **251,16 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Unmanaged
- ✓ Basic switching RJ-45 Ethernet ports quantity: 5
- ✓ 10BASE-T, 100BASE-TX, 1000BASE-T
- ✓ MAC address table: 1000 entries Switching capacity: 10 Gbit/s
- ✓ Power over Ethernet (PoE)



Aprašymas

The LevelOne GEP-0521 provides 5 x 10/100/1000Base-T PoE-Plus ports. This switch is IEEE 802.3af/at compliant, providing power and data over a single Ethernet cable to any PoE device, with total power budget of 120W, up to 30W per port. Together with Energy Efficient Ethernet (IEEE 802.3az) standard compliant, it substantially lower power consumption during periods of low-link utilization. Moreover, it supports Gigabit Ethernet connectivity with 9K jumbo frames for network performing enhancement. Ideal for small businesses that prefers an inexpensive solution for PoE deploying infrastructure.

Key Features

- IEEE 802.3af/at PoE compliant to simplify deployment and installation
- 10/100/1000Mbps wire speed transmission and reception
- 9K jumbo frames to increase data transfer rates
- Auto-detection and protection of non-standard PoE devices

- IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- Total PoE power budget: 120W, up to 30W per port
- Minimize carbon footprint with advanced energy efficient technology (IEEE 802.3az)

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Management features	
Switch type	Unmanaged
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	5
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Power connector	DC-in jack
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Full duplex	Yes
Flow control support	Yes
Cable length detection	Yes
MAC address auto-learning supported	Yes
MAC address auto-aging supported	Yes
Data transmission	
MAC address table	1000 entries
Switching capacity	10 Gbit/s
Store-and-forward	Yes
Jumbo frames support	Yes
Jumbo frames	8000
Packet forwarding rate (1 Gbps)	1488000 pps
Packet forwarding rate (100 Mbps)	148000 pps
Packet forwarding rate (10 Mbps)	14880 pps
Design	
Product colour	Grey

LED indicators	Activity, PoE, Power
Performance	
Buffer size	104 KB
Power	
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (typical)	120 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet plus (PoE+) ports quantity	4
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	140 W
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width	120 mm
Depth	90 mm
Height	28 mm
Weight	800 g
Packaging content	
Quick start guide	No
Packaging data	
AC adapter included	Yes
Package width	148 mm
Package depth	80 mm
Package height	232 mm
Package weight	1 kg
Certificates	
Certification	FCC Part 15 Class A, CE, RoHS
Logistics data	
Harmonized System (HS) code	85176990

Matmenys ir svoris

Svoris	0,99kg
--------	--------