

Lindy 70m Fibre Optic Hybrid Mini DisplayPort 1.4 Cable with Detachable DP Connectors

Gamintojas: **LINDY** · Modelis: **38485** · EAN: **4002888384858** · Prekės kodas: **743458**



590,90 €

Kaina su PVM

Be PVM: **488,35 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Combines copper and fibre optic cable for a hybrid, long distance Mini DP and DP connectivity solution
- ✓ Supplied as a Mini DisplayPort Male to male cable, with detachable DisplayPort connectors
- ✓ Supports DP 1.4 resolutions up to 8K@60Hz, 4K@120Hz with additional support for static and dynamic HDR
- ✓ No external power required
- ✓ 2 year warranty



Aprašymas

Lindy's range of Fibre Optic Hybrid Mini DP 1.4 Cable with detachable connectors are the professional solution for extending both Mini DisplayPort and DisplayPort signals over longer distances, with no requirement for additional adapters. Combining the flexibility and high EMI and RFI resistance of fibre optic cable with standard copper cabling, these hybrid cables are ideal for use in critical AV setups or commercial installations.

Supplied as a thin cable with a premium metal, narrow Mini DisplayPort connector, this can be installed easily through conduit and other narrow spaces with no damage caused to the internal cable structure, while the detachable DisplayPort connector can be added at the ends of the installation for connection to an even wider variety of displays and devices such as PCs or digital signage. This innovative design allows for a much wider range of connectivity solutions that can be customized freely by the user, including Mini DP to Mini DP, DP to DP or Mini DP to a DP display.

Supporting all the premium features that come with the DP 1.4 specification, these cables can deliver resolutions up to 8K at 60Hz, or 4K at high frame rates of 120Hz, perfect for ensuring the best possible image quality in attention grabbing retail displays, immersive AV installations at events or a responsive, crystal-clear solution in transportation settings. Static and dynamic HDR support ensures a much wider colour gamut, greater contrasts and an enhanced brightness to provide eye-catching content even in outdoor or brightly lit scenarios.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Kabel und Adapter > Displayport Kabel und Adapter [+1987][-131]
Features	
Cable length	70 m
Connector 1	Mini DisplayPort
Connector 2	Mini DisplayPort
Connector 1 gender	Male
Connector 2 gender	Male
Maximum resolution	7680 x 4320 pixels
Product colour	Black
Connector contacts plating	Gold
DisplayPort version	1.4
Supported graphics resolutions	4096 x 2160, 7680 x 4320
Supported video modes	2160p, 4320p
Maximum refresh rate	120 Hz
Jacket material	Polyvinyl chloride (PVC)
Data transfer rate	32.4 Gbit/s
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-25 - 85 °C
Certificates	
Compliance certificates	RoHS
Weight & dimensions	
Cable diameter	4.8 mm
Logistics data	
Harmonized System (HS) code	84733080
Matmenys ir svoris	
Svoris	3,14kg