

TP-Link Omada ES208G network switch Managed L2 Gigabit Ethernet (10/100/1000) Black

Gamintojas: **TP-LINK** · Modelis: **ES208G** · EAN: **1210002600668** · Prekės kodas: **743933**



37,90 €

Kaina su PVM

Be PVM: **31,32 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 8x 10/100/1000Mbps RJ45 ports
- ✓ Easy to Use: Supports plug-and-play for instant connectivity and simple configuration for additional features
- ✓ Centralized Cloud Management via the web or the Omada app
- ✓ VLAN, Port Isolation, Cable Test, QoS for reliable surveillance networking
- ✓ Automatic Loop Prevention and IGMP Snooping
- ✓ Fanless design for silent operation
- ✓ Durable metal casing and desktop/wall mounting design



Aprašymas

Omada Cloud Essentials — A Free and Easy Cloud-Based Network Management

Omada Cloud Essentials is a free, easy-to-use version of the Omada Cloud-based Controller. It provides cloud-based centralized management and monitoring for the Omada networking system, covering access points, switches, and gateways, ideal for surveillance networks and small businesses.

Techninė specifikacija

Specifications

Sandėlio grupė > Netzwerk > Switches [+1607][-273]

Management features

Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
Cloud-managed	Yes
Unified static configuration	Yes

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	8
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Gigabit Ethernet (copper) ports quantity	8

Network

Networking standards	IEEE 802.3ab, IEEE 802.1ab, IEEE 802.3i, IEEE 802.1p, IEEE 802.3x, IEEE 802.3at, IEEE 802.1Q
10G support	No
Zero Touch Provisioning (ZTP)	Yes
Port mirroring	Yes
Flow control support	Yes
Link aggregation	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Fast leave	Yes
VLAN support	Yes
Virtual LAN features	MTU VLAN, Port-based VLAN, Tagged VLAN
Number of VLANs	32

Data transmission

MAC address table	8000 entries
Switching capacity	16 Gbit/s
Forwarding rate	11.9 Mpps
Store-and-forward	Yes
Jumbo frames support	Yes
Jumbo frames	15000
Packet buffer memory	4 MB

Security

DHCP features	DHCP client
IGMP snooping	Yes
Loop protection	Yes
Queue scheduling algorithms	Weighted Round Robin (WRR)

Design

Rack mounting	No
Stackable	No
Product colour	Black
LED indicators	Yes
Wall mountable	Yes

Performance

Flash memory	64 MB
Firmware upgradeable	Yes
Fanless	Yes
Mean time between failures (MTBF)	1141726 h

Power

Power source	DC
Power supply included	Yes
DC input voltage	5 V
Input current	0.6 A
Power consumption (max)	2.7 W
Surge protection	Yes
Surge protection voltage	6 kV

Power over Ethernet (PoE)

Power over Ethernet (PoE)	No
---------------------------	----

Operational conditions

Operating temperature (T-T)	-5 - 45 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Heat dissipation	9.09 BTU/h

Weight & dimensions

Width	158 mm
-------	--------

Depth	100.7 mm
Height	25.4 mm
Packaging content	
User guide	Yes
Packaging data	
AC adapter included	Yes
Package type	Box
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
Matmenys ir svoris	
Matmenys (I × P × A)	13,00cm × 19,00cm × 9,00cm
Svoris	0,65kg