



## UPS EATON 420 Watts 700 VA Offline 3S700D



Modelis: 3S700D

Gamintojas: EATON

EAN: 743172101761

Prekės kodas: 74428

# 121.99€

Eaton 3S provides power and surge protection for desktop computers, wireless networks, gaming consoles, and other critical equipment in your home or business.

- Eaton 3S supplies battery backup power during outage and advanced surge protection to prevent damage from lightning strikes or accidental grid surge
- Compact and appealing design with glossy finish will perfectly fit in any modern residential or office environment
- To facilitate installation, wall mounting system is implemented on all models
- Surge protection circuits are compliant with IEC 61643-11 international standard
- 10A circuit breaker protects your equipment from overload (all models)
- Eaton offers free warranty for the equipment connected (applicable in EU countries and Norway only). This guarantee is included in the purchase price of all Eaton 3S products and covers unlimited warranty, covering damage due to the surge protection failure

Summary: Eaton 3S700D. UPS topology: Standby (Offline), Output power capacity: 0.7 kVA, Output

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

power: 420 W. AC outlet types: Type F, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA). Product colour: Black, White, Cable length: 1.5 m. Certification: CE/EAC/Ukr/Cm/CB report | Vendor Homepage: <https://www.eaton.com> | Input frequency: 50/60 | Input operation voltage (max): 284 | Input operation voltage (min): 161 | Maximum current: 10 | Output frequency: 50 | Output operation voltage (max): 240 | Output operation voltage (min): 220 | Output power: 420 | Output power capacity: 0.7 | Power protection features: Overdischarge | Surge protection: Yes | UPS topology: Standby (Offline) | AC outlet types: Type F | AC outlets quantity: 8 | USB 2.0 ports quantity: 2 | USB port: Yes | Automatic battery test: Yes | Battery technology: Sealed Lead Acid (VRLA) | Cold start: Yes | Hot-swap battery: No | Cable length: 1.5 | LED indicators: Yes | Product colour: Black,White | Operating altitude: 0 - 3000 | Operating temperature (T-T): 0 - 40 | Certification: CE/EAC/Ukr/Cm/CB report | Safety: IEC 62040-1; IEC 62040-2 C2; IEC 62040-3; IEC 62040-4; IEC 61643-11 | Depth: 170 | Height: 86 | Weight: 4000 | Width: 335 | Harmonized System (HS) code: 85078000 | Nominal input voltage: 230 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.01568 | Unit Calculated Weight: 4.7

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903