

Lindy 10m USB 3.0 Active Extension Pro

 Gamintojas: **LINDY** · Modelis: **43157** · EAN: **4002888431576** · Prekės kodas: **746010**


99,90 €

Kaina su PVM

 Be PVM: **82,56 €**



Sandėlyje


Prekė internetu

 Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ High performance, active cable that provides an extended 10m connection between a computer and USB 3.0 device
- ✓ Can be used standalone or as part of the Lindy Active Extension System Pro to create bespoke extension systems of over 40m (depending on the cable configurations used)
- ✓ Supports the full USB 3.0 SuperSpeed bandwidth for speeds of 5Gbps
- ✓ Easy to use ? connects to the device’s existing USB cable (2m maximum)
- ✓ 2 year warranty



Aprašymas

The Lindy 10m USB 3.0 Active Extension Cable Pro is a high-performance cable that allows a computer to connect to USB 3.0 SuperSpeed peripherals over long distances. It supports data transfer speeds of up to 5Gbps, making it ideal for quickly and reliably transferring large amounts of data.

The cable incorporates proven active technology and locking connectors to ensure reliable signal integrity, even in demanding environments.

This 10m extension cable can be used on its own or as part of the Lindy USB 3.0 Active Extension System Pro. This system is a modular solution that combines multiple USB Active Extension Pro cables and a USB 3.0 Active Extension Pro hub. It enables the distribution of USB signals to up to 4

devices at distances of up to 40m (depending on the cable configurations used).

Using this cable as part of the USB 3.0 Active Extension System Pro

If you would like to use this cable as part of combined Lindy USB 3.0 Active Extension System Pro installation, please note the requirements below.

The first unit connected to your computer must always be the USB 3.0 Active Extension Pro 8m (No. 43158) or 15m (No. 43229). Once the first cable is connected, you can cascade additional Extension System Pro cables to extend the distance up to a maximum of 40m.

The final part of the extension can be any cable or hub from the Extension System Pro range.

If you need to extend multiple devices or connect a USB device with high power requirements, you should use the 10m Hub Pro unit (No. 43159) with its power supply as the final part of the extension.

Information about USB 3.0, 3.1 and 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface. USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps. USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

Techninė specifikacija

Specifications	
Sandėlio grupė	USB [+3386][-35]
Features	
USB version	USB 3.2 Gen 1 (3.1 Gen 1)
Connector 1	USB A
Connector 2	USB A
Connector 1 gender	Male
Connector 2 gender	Female
Product colour	Black
Connector 1 form factor	Straight
Connector 2 form factor	Straight
AWG wire size	24/24/20
Connector material	Nickel
Contact material	Brass
Connector contacts plating	Gold
Cable jacket material	Polyvinyl chloride (PVC)
Conductor material	Tinned copper
Connector shielding	Yes
Connector shield material	Aluminium
Connector housing material	Plastic

Maximum data transfer rate	5000 Mbit/s
Maximum data transfer rate	5 Gbit/s
Cable type	Round cable
Transmission medium	Twisted pair
Nominal attenuation	0.064MHz - 0.08dB 0.256MHz - 0.11dB 0.512MHz - 0.13dB 0.772MHz - 0.15dB 1.0MHz - 0.20dB 4MHz - 0.39dB 8MHz - 0.57dB 12MHz - 0.67dB 24MHz - 0.95dB 48MHz - 1.35dB 96MHz - 1.90dB 200MHz - 3.20dB 400MHz - 5.80dB

Power

Power note	2.5/0.7mm DC
------------	--------------

Weight & dimensions

Cable length	10 m
Cable diameter	7 mm
Weight	750 g
Bend radius (min)	3.6 cm
Connector 1 dimensions (WxDxH)	15 x 49 x 8 mm
Connector 2 dimensions (WxDxH)	20 x 80 x 13 mm

Packaging data

Package type	Box
Package width	240 mm
Package depth	70 mm
Package height	200 mm
Package weight	900 g

Packaging content

Quantity per pack	1 pc(s)
Manual	Yes

Operational conditions

Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C

Certificates

Certification	CE, UKCA, FCC, RoHS, REACH, California Proposition 65
---------------	---

Logistics data

Harmonized System (HS) code	84733080
-----------------------------	----------

Matmenys ir svoris

Matmenys (l × P × A)	24,00cm × 21,00cm × 7,00cm
Svoris	0,93kg