

Lindy 73424 mobile device charger Universal White AC Fast charging Indoor

Gamintojas: **LINDY** · Modelis: **73424** · EAN: **4002888734240** · Prekės kodas: **746038**



22,91 €

Kaina su PVM

Be PVM: **18,93 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Charges and powers two devices simultaneously via a USB Type C and a USB Type A port
- ✓ 30W Power Delivery via the USB Type C port provides fast charging for smartphones, tablets, laptops and other mobile devices
- ✓ Compact design for maximum mobility
- ✓ Built-in safety features such as overvoltage and overcurrent protection



Aprašymas

The Lindy 30W USB Type A & C PD Charger can charge two devices simultaneously. 30W Power Delivery are supported by the USB Type C port while the USB Type A port provides fast charging with up to 18W. When both ports are used in parallel a maximum power of 15W will be provided.

Featuring both a USB Type C female and a USB Type A female port this charger is ideal for use with most popular smartphones and iOS devices. Supporting power delivery of 30W, connected devices can be provided with faster charging than what is possible from a standard Type C or A charger supplied with many devices.

For safe charging the device includes overcharge, overcurrent, overtemperature and short circuit protection. As this charger is rated at Level 6 for efficiency, it also meets the highest current level of energy efficiency standards.

Techninė specifikacija

Specifications	
Sandėlio grupė	USB [+3386][-35]
Performance	
Charger type	Indoor
Charger compatibility	Universal
Power source type	AC
Number of simultaneously connected devices (max)	2
USB 2.0 ports quantity	1
USB Type-C ports quantity	1
Fast charging	Yes
Fast charging technology	Power Delivery 3.0
USB Power Delivery (USB PD)	Yes
USB Power Delivery revision	3
USB Power Delivery up to	30 W
Power protection features	Over current, Over voltage, Overheating, Short circuit
Design	
Product colour	White
Housing material	Polyvinyl chloride (PVC)
Connector material	Copper
Power	
Input voltage	100 - 240 V
Input frequency	50/60 Hz
Input current	0.6 A
Maximum power	30 W
Maximum output voltage	20 V
Minimum output voltage	5 V
Output voltage accuracy (±)	5%
Output current (5V)	3 A
Output current (9V)	3 A
Output current (12V)	2.5 A
Output current (15V)	2 A
Output current (20V)	1.5 A
Power consumption (no load)	0.1 W

Average active efficiency	81.38%
Efficiency at low load (10%)	Yes
Weight & dimensions	
Width	26.8 mm
Depth	85.3 mm
Height	41.6 mm
Weight	40 g
Packaging data	
Package width	80 mm
Package depth	100 mm
Package height	45 mm
Package weight	60 g
Package type	Box
Operational conditions	
Operating temperature (T-T)	0 - 25 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	20 - 90%
Storage relative humidity (H-H)	20 - 90%
Packaging content	
Quantity per pack	1 pc(s)
Manual	Yes
Certificates	
Compliance certificates	CE, REACH, RoHS
Sustainability	
Sustainability certificates	ErP
Sustainability compliance	Yes
Matmenys ir svoris	
Matmenys (I × P × A)	15,00cm × 3,00cm × 8,00cm
Svoris	0,08kg