

LogiLink WL0247 network card WLAN 1300 Mbit/s

Gamintojas: **LOGILINK** · Modelis: **WL0247** · EAN: **4052792061154** · Prekės kodas: **746226**



38,90 €

Kaina su PVM

Be PVM: **32,15 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Complies with IEEE 802.11ac/a/b/g/n standards
- ✓ Data transfer rate up to 600Mbps (2.4GHz) or up to 1300Mbps (5GHz)
- ✓ Supports 64/128-bit WEP, WPA/WPA2 and WPA-PSK/WPA2-PSK (TKIP/AES) encryption
- ✓ Supports Beam Forming function
- ✓ Bandwidth transmission up to 80MHz
- ✓ Supports Windows, Linux and Mac OS
- ✓ With extension cable USB base



Aprašymas

Product information "Wireless LAN 802.11ac USB 3.0 adapter, 2T2R, with USB base" from LogiLink

Mobile Wireless LAN USB 3.0 adapter from LogiLink. Fast data transfer rates of up to 600 MBit/s at 2.4 GHz and 1300 MBit/s at 5 GHz, supports IEEE 802.11ac/a/b/g/n. 64/128 Bit WEP, WPA/WPA2 and WPA-PSK/WPA2-PSK (TKIP/AES) encryption provides optimal security. The WL0247 also supports beamforming function and includes an extension cable with USB base.

Techninė specifikacija

Specifications

Sandėlio grupė	USB [+3386][-35]
Ports & interfaces	
Connectivity technology	Wireless
Host interface	USB
Interface	WLAN
USB version	3.2 Gen 1 (3.1 Gen 1)
Network	
Maximum data transfer rate	1300 Mbit/s
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Wi-Fi	Yes
Wi-Fi band	Dual-band (2.4 GHz / 5 GHz)
Top Wi-Fi standard	Wi-Fi 5 (802.11ac)
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
WLAN data transfer rates supported	11,54,600,1300 Mbit/s
Security algorithms	64-bit WEP, 128-bit WEP, AES, TKIP, WPA, WPA-PSK, WPA2, WPA2-PSK, WPS
Design	
Internal	No
Component for	PC/Laptop
Product colour	Black
Antenna	Yes
Antenna design	External
System requirements	
Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows 8.1
Mac operating systems supported	Yes
Linux operating systems supported	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	5 - 95%
Logistics data	
Harmonized System (HS) code	85176990