

Conceptronic 6-Port 200W GaN USB PD Charger with USB-C Charging Cable, USB-C x 4, USB-A x 2, QC 3.0, PD 3.1, PPS

Gamintojas: **CONCEPTRONIC** · Modelis: **OZUL06BE** · EAN: **4015867236543** · Prekės kodas: **746267**



131,90 €

Kaina su PVM

Be PVM: **109,01 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ **High-Power GaN Technology:** This charger utilizes advanced Gallium Nitride (GaN) technology, providing up to 200W of total power for faster and more efficient charging.
- ✓ **Enhanced Safety Features:** Built-in protections against overload, short circuiting, and overheating, ensuring the safety of both the charger and connected devices.
- ✓ **Versatile Port Selection:** Equipped with 6 ports including 4 USB-C ports (with PD 3.1) and 2 USB-A ports (with QC 3.0), allowing simultaneous charging for multiple devices with varying power requirements.
- ✓ **Efficiency and Quick Charge Technology:** Incorporates USB Power Delivery (PD) 3.1 and Quick Charge (QC) 3.0 technologies for rapid charging, along with Programmable Power Supply (PPS) compliance to maximize charging efficiency and minimize heat generation.
- ✓ **Wide Compatibility:** Supports a range of output options from 20W to 140W across its ports, ensuring compatibility with devices from smartphones to laptops.



Aprašymas

The PD 3.1 USB Charger offers efficient and ultra-fast charging with Power Delivery (PD) 3.1 technology. It features a single USB-C port capable of delivering up to 140W of power, perfect for charging devices such as MacBook Pro 16", MacBook Air, Dell laptops, Nintendo Switch, and more. This 6-in-1 charger includes 4 USB-C ports and 2 USB-A ports, providing a total output of up to 200W to accommodate various charging power needs. Moreover, this GaN 2 charger utilizes gallium nitride (GaN) technology, offering a smaller and more streamlined alternative to traditional silicon

chargers. Compared to GaN 1 chargers, it generates less heat, resulting in greater efficiency and more power directed to the device rather than being lost.

For safety, the charger is protected against overload, short-circuiting, and overheating. It's an ideal all-in-one charging solution for daily use, providing efficient and reliable power delivery for all your devices.

Techninė specifikacija

Specifications	
Sandėlio grupė	USB [+3386][[-35]
Performance	
Charger type	Indoor
Charger compatibility	Universal
Power source type	AC
Number of simultaneously connected devices (max)	6
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
USB Type-C ports quantity	4
Fast charging	Yes
Fast charging technology	Power Delivery, Quick Charge 3.0
USB Power Delivery (USB PD)	Yes
USB Power Delivery revision	3.1
USB Power Delivery up to	140 W
Power protection features	Overheating, Overload, Short circuit
Design	
Product colour	Black
Gallium nitride (GaN) transistors	Yes
Power	
Input voltage	100 - 240 V
Input frequency	50 - 60 Hz
Input current	2.5 A
Maximum power	200 W
Maximum output voltage	55 V
Minimum output voltage	3.3 V
Port 1 output power	140 W
Port 2 output power	140 W
Port 3 output power	45 W
Port 4 output power	20 W
Port 5 output power	18 W

Port 6 output power	18 W
Output current (5V)	3 A
Output current (9V)	3 A
Output current (12V)	3 A
Output current (15V)	3 A
Output current (20V)	5 A
Port 1 output current	5 A
Port 2 output current	5 A
Port 3 output current	4.05 A
Port 4 output current	3 A
Port 5 output current	3 A
Port 6 output current	3 A
Weight & dimensions	
Width	53.5 mm
Depth	112.5 mm
Height	53.5 mm
Weight	450 g
Packaging data	
Package width	160 mm
Package depth	57 mm
Package height	150 mm
Package weight	735 g
Package type	Box
Operational conditions	
Operating temperature (T-T)	0 - 35 °C
Storage temperature (T-T)	-20 - 80 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	10 - 90%
Packaging content	
Cables included	AC, USB Type-C to USB Type-C
Logistics data	
Harmonized System (HS) code	8504408390
Pallet gross width	120 cm
Pallet gross length	80 cm

Pallet gross height	152 cm
Master (outer) case width	335 mm
Master (outer) case length	320 mm
Master (outer) case height	300 mm
Master (outer) case gross weight	15.2 kg
Products per master (outer) case	20 pc(s)
Country of origin	China
Other features	
Number of products included	1 pc(s)
User guide	Yes
Sustainability	
Sustainability compliance	Yes