

Conceptronic ETTA07B12 USB 3.2 Gen 2x2 C-C PD 3.0 100W Cable 1.2M, 20V 5A, 20Gbps, 4K60Hz, E-Mark

Gamintojas: CONCEPTRONIC · Modelis: ETTA07B12 · EAN: 4015867241417 · Prekės kodas: 746274



11,89 €

Kaina su PVM

Be PVM: 9,83 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ USB-C male to USB-C male cable
- ✓ With E-mark Chipset
- ✓ Power Delivery supports up to 20V/5A, max. 100W
- ✓ Data transfer rate of up to 20Gbps
- ✓ Robust and flexible braided cable for extended durability



Aprašymas

The Conceptronic USB-C cable is designed for high-speed performance and reliable power delivery. Supporting USB 3.2 Gen 2x2 with data transfer speeds of up to 20Gbps, it enables fast and efficient file transfers. Built with PD 3.0 technology and an integrated E-Mark chipset, the cable delivers up to 100W (20V/5A) of charging power, making it ideal for laptops, tablets, and other power-hungry devices.

Its durable braided exterior provides added strength and flexibility, making it perfect for everyday use at home, in the office, or on the go. With support for video resolutions up to 4K at 60Hz, it offers sharp, detailed visuals for all your multimedia needs. Dependable, multifunctional, and engineered for performance, the Conceptronic USB-C cable is the ultimate solution for charging, data transfer, and display connectivity.

Techninė specifikacija

Specifications	
Sandėlio grupė	USB [+3386][[-35]
Features	
USB version	USB 3.2 Gen 2x2
Connector 1	USB C
Connector 2	USB C
Connector 1 gender	Male
Connector 2 gender	Male
Product colour	Black
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Conductor material	Copper
Maximum data transfer rate	20 Gbit/s
Cable type	Round cable
Fast charging	Yes
USB Power Delivery (USB PD)	Yes
USB Power Delivery revision	3
USB Power Delivery up to	100 W
Maximum resolution	3840 x 2160 pixels
Maximum refresh rate	60 Hz
Power	
Output voltage	20 V
Output current (max)	5 A
Weight & dimensions	
Cable length	1.2 m
Width	3.8 mm
Depth	3.8 mm
Height	1200 mm
Weight	30 g
Packaging data	
Package width	60 mm
Package depth	34 mm
Package height	120 mm
Package weight	40 g

Packaging content

Quantity per pack	1 pc(s)
-------------------	---------

Operational conditions

Operating temperature (T-T)	-40 - 85 °C
-----------------------------	-------------

Certificates

Compliance certificates	CE, REACH, RoHS
-------------------------	-----------------

Logistics data

Products per master (outer) case	100 pc(s)
----------------------------------	-----------

Master (outer) case width	400 mm
---------------------------	--------

Master (outer) case length	200 mm
----------------------------	--------

Master (outer) case height	300 mm
----------------------------	--------

Master (outer) case gross weight	4.5 kg
----------------------------------	--------

Pallet gross width	120 cm
--------------------	--------

Pallet gross length	80 cm
---------------------	-------

Pallet gross height	195.2 cm
---------------------	----------

Harmonized System (HS) code	8544429000
-----------------------------	------------

Country of origin	China
-------------------	-------