

Equip USB4 Gen 2x2 C to C Cable, 3.0m, PD 100W, 4K/60Hz, 20Gbps, Black

Gamintojas: **EQUIP** · Modelis: **128384** · EAN: **4015867243688** · Prekės kodas: **746359**



26,90 €

Kaina su PVM

Be PVM: 22,23 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ USB 4 Gen 2x2
- ✓ USB-C to C Male
- ✓ 20Gbps data transfer rate
- ✓ with E-mark Chipset
- ✓ Power Delivery support up to 20V/5A, Max. 100W
- ✓ Support of USB Power Delivery (PD)
- ✓ Resolution: up to 4K@60 Hz
- ✓ Supports HDR10
- ✓ Supports HDCP 1.4 and 2.3
- ✓ Supports PCI Express 3.0 protocol



Aprašymas

The 128384 USB4 Gen 2x2 C to C cable is designed for high-speed data transfer, ultra-high power delivery, and advanced display support for modern USB-C devices.

Built on USB4 Gen 2x2 architecture, it supports data transfer speeds of up to 20Gbps, making it ideal for fast file transfers, external SSDs, and high-bandwidth peripherals. With an integrated E-marker chipset and USB Power Delivery 3.1 support, the cable delivers up to 240W (48V/5A), enabling safe and stable charging for power-hungry laptops, workstations, and docking setups.

The cable also supports video output up to 4K@60Hz via DP Alt Mode and is compatible with DisplayPort 1.4a, HDR10, HDCP standards, and PCI

Express 3.0 protocol. Fully compatible with USB 3.2, USB 2.0, and Thunderbolt 3 devices, it offers broad device interoperability while ensuring reliable performance for professional and everyday use.

Techninė specifikacija

Specifications	
Sandėlio grupė	USB [+3386][-35]
Features	
USB version	USB4 Gen 2x2
Connector 1	USB C
Connector 2	USB C
Connector 1 gender	Male
Connector 2 gender	Male
Product colour	Black
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Cable jacket material	Cotton
Conductor material	Copper
Maximum data transfer rate	20 Gbit/s
Cable type	Round cable
Plug and Play	Yes
Fast charging	Yes
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	240 W
USB Type-C DisplayPort Alternate Mode	Yes
DisplayPort version	1.4a
Maximum resolution	3840 x 2160 pixels
High Dynamic Range (HDR) supported	Yes
High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)
HDCP	Yes
HDCP version	1.4/2.3
Power	
Input voltage	48 V
Input current (max)	5 A
Weight & dimensions	
Cable length	3 m

Width	48 mm
Depth	48 mm
Height	3000 mm
Weight	140 g
Packaging data	
Package type	Polybag
Package width	275 mm
Package depth	10 mm
Package height	175 mm
Package weight	140 g
Packaging content	
Quantity per pack	1 pc(s)
Certificates	
Compliance certificates	CE, RoHS, REACH
Logistics data	
Products per master (outer) case	80 pc(s)
Master (outer) case width	330 mm
Master (outer) case length	280 mm
Master (outer) case height	390 mm
Master (outer) case gross weight	11.7 kg
Customs product code (TARIC)	8544421000
Country of origin	China