

Dahua Technology DHI-ASC3202B access control reader Basic access control reader White

Gamintojas: **DAHUA** · Modelis: **DHI-ASC3202B** · EAN: **6923172500106** · Prekės kodas: **746599**



594,90 €

Kaina su PVM

Be PVM: **491,65 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Built-in Web server, features main and sub control modes
- ✓ The main control mode offers access control Platform functions, can connect with and manage up to 19 sub controllers. The sub-control modes can be added to multiple platforms
- ✓ Supports 1000 users, 3000 fingerprints, and 300,000 records
- ✓ Accesses card readers through Wiegand and RS-485 protocols
- ✓ Supports TCP and IP connection, and standard PoE
- ✓ Supplies power to the lock through its 12 VDC output power supply, which has a maximum output current of 1000 mA
- ✓ Supports configuring the hardware I/O port and exporting configuration diagrams
- ✓ Retains stored data even while powered off



Aprašymas

Dahua CCTV Controller DHI-ASC3202B (DHI-ASC3202B)

Techninė specifikacija

Specifications

Sandėlio grupė

> Netzwerk > Netzwerkkamera und Zubehör [+1996][-361]

Technical details

Type	Basic access control reader
Authentication type	Access chip/card, Password
Fingerprint reader	Yes
Access code reader	No
Access chip/card reader	Yes
Buzzer	Yes
Wiegand interface	Yes
Tamper protection	Yes
Cards capacity	5000 cards
Fingerprint capacity	3000
Alarm input channels	2
Alarm output channels	2
User capacity	1000 user(s)
Record capacity	300000
Interoperability	ONVIF; CGI
Software development kit (SDK) support	Yes
Exit button	Yes
Lock control	Yes
Web-based management	Yes
Unlock function	Yes
Real-time surveillance	Yes
Duress alarm	Yes
Compliance certificates	CE, Federal Communications Commission (FCC)
Product colour	White
Housing material	Acrylonitrile butadiene styrene (ABS), Polycarbonate (PC)
IK code	IK06

Display

Built-in display	No
------------------	----

Camera

Front camera	No
--------------	----

Ports & interfaces

Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	10,100 Mbit/s

Cabling technology	10/100
Supported network protocols	P2P; IPv4; DNS; DDNS; TCP; UDP
RS-485 ports	3
Power	
Power over Ethernet (PoE)	Yes
DC voltage range	12 V
Power consumption	1700 mA
Weight & dimensions	
Width	185.8 mm
Depth	186.4 mm
Height	58.3 mm
Weight	990 g
Packaging data	
Package width	243 mm
Package depth	254 mm
Package height	86 mm
Operational conditions	
Operating temperature (T-T)	-10 - 55 °C
Operating relative humidity (H-H)	5 - 95%
Sustainability	
Sustainability compliance	Yes
Matmenys ir svoris	
Svoris	1,00kg