

TP-Link Omada SG3428XMPP network switch Managed L2+ Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Black

Gamintojas: **TP-LINK** · Modelis: **SG3428XMPP** · EAN: **8885020620856** · Prekės kodas: **747163**



708,90 €

Kaina su PVM

Be PVM: **585,87 €**

[Sandėlyje](#)



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 8x Gigabit 802.af/at/bt PoE++ ports (Max 90 W PoE budget for each port)
- ✓ 16x Gigabit 802.3af/at PoE+ ports (Max 30 W budget for each port)
- ✓ 500 W total PoE budget*
- ✓ Centralized cloud management via the web or the Omada app†
- ✓ Standalone management via web, CLI, SNMP, and RMON
- ✓ Static Routing, VLAN, ACL, QoS, IGMP Snooping, OAM, and DDM
- ✓ ERPS supports rapid protection and recovery in a ring topology
- ✓ Durable metal casing and rack-mountable design



Aprašymas

Empowering the High-Power Devices with Gigabit PoE++ Ports

Easily Build a Whole 10G Multi-gigabit Network

Software Defined Networking (SDN) with Cloud Access

Remotely manage your access points, switches, and gateways across multiple sites all from a single interface.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Management features	
Switch type	Managed
Switch layer	L2+
Quality of Service (QoS) support	Yes
Web-based management	Yes
Cloud-managed	Yes
ARP inspection	Yes
Configuring Location Settings (CLI)	Yes
System event log	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	24
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
SFP+ module slots quantity	4
Console port	RJ-45/Micro-USB
Power connector	AC-in jack
Network	
Networking standards	IEEE 802.3af, IEEE 802.3at
10G support	Yes
Port mirroring	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Rate limiting	Yes
Spanning tree protocol	Yes
Head-of-line (HOL) blocking	Yes
VLAN support	Yes
Data transmission	
MAC address table	16000 entries
Switching capacity	128 Gbit/s
Forwarding rate	95.23 Mpps
Store-and-forward	Yes

Jumbo frames support	Yes
Jumbo frames	9000
Packet buffer memory	12 MB
Security	
DHCP features	DHCP client, DHCP relay, DHCP server
Access Control List (ACL)	Yes
IGMP snooping	Yes
MAC address filtering	Yes
Static port security	Yes
SSH/SSL support	Yes
BPDU filtering/protection	Yes
IP-MAC-Port binding	Yes
Authentication	Auto VLAN, Guest VLAN
Multicast features	
Multicast support	Yes
Design	
Rack mounting	Yes
Form factor	1U
Product colour	Black
Reset button	Yes
LED indicators	Yes
Number of fans	3 fan(s)
Power	
Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (max)	486.2 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet plus (PoE+) ports quantity	16
Power over Ethernet 4PPoE (PoE++) ports quantity	8
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	500 W

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Heat dissipation	1658.78 BTU/h

Weight & dimensions

Width	440 mm
Depth	330 mm
Height	44 mm

Packaging content

Cables included	AC
Quick start guide	Yes

Certificates

Certification	CE, FCC, RoHS
---------------	---------------

Matmenys ir svoris

Matmenys (I × P × A)	47,00cm × 55,00cm × 10,00cm
Svoris	6,26kg