

Bosch DINION thermal 8100i Bullet IP security camera Indoor & outdoor 640 x 480 pixels Ceiling/wall

Gamintojas: **BOSCH** · Modelis: **NBT-8701-F25VF** · EAN: **4060039192257** · Prekės kodas: **747835**



10 857,90 €

Kaina su PVM

Be PVM: **8 973,47 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Indoor & outdoor IP security camera
- ✓ Microbolometer 0.3 MP 640 x 480 pixels
- ✓ Wired Ethernet LAN
- ✓ Night vision
- ✓ Bullet Ceiling/wall
- ✓ IP66, IP67 IK10
- ✓ White
- ✓ 2.95 kg

Aprašymas

Bosch Bullet thermal VGA 17° 30Hz (NBT-8701-F25VF)

Techninė specifikacija

Specifications

Sandėlio grupė > Netzwerk > Netzwerkkamera und Zubehör [+1996][+361]

Performance

Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
Thermal module	Yes
Maximum operating distance	622 m

Alarm input/output	Yes
Remote viewing	Yes
Thermal sensitivity (NETD)	30 mK

Design

Mounting type	Ceiling/wall
Product colour	White
Form factor	Bullet
Housing material	Aluminium, Cement
International Protection (IP) code	IP66, IP67
IK code	IK10

Camera

Vertical field of view (thermal module)	13°
Horizontal field of view (thermal module)	17°
Number of Privacy masking areas	8

Image sensor

Sensor type	Microbolometer
Sensor type (thermal module)	Noise equivalent temperature difference (NETD)
Effective sensor resolution (thermal module)	640 x 480 pixels

Lens system

Number of lenses	1
Fixed focal length	25 mm

Night vision

Night vision	Yes
--------------	-----

Video

Maximum resolution	640 x 480 pixels
Total megapixels	0.3 MP
Video formats supported	H.264, M-JPEG, HEVC/H.265
Frame rate	30 fps
Video streaming	Yes
Image quality adjustment	Brightness, Contrast, Sharpness

Audio

Audio system	2-way
Audio system full duplex	Yes
Audio formats supported	AAC-LC

Sample rate	16 kHz
Signal-to-Noise Ratio (SNR)	50 dB
Network	
Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Ethernet interface type	Fast Ethernet
Storage	
Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	MicroSDHC, MicroSDXC
Maximum memory card size	2 TB
Flash memory	8192 MB
RAM capacity	2048 MB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Microphone in	Yes
USB port	Yes
Security	
Video motion detection	Yes
Privacy protection	Yes
Management features	
Cloud-managed	Yes
Power	
Power source type	PoE, DC, AC
AC input voltage	24 V
Power consumption (Power over Ethernet (PoE))	12.9 W
Operational conditions	
Operating temperature (T-T)	-40 - 55 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 95%
Weight & dimensions	
Width	352 mm
Diameter	14.8 cm

Weight	2.95 kg
Sustainability	
Compliance certificates	National Defense Authorization Act (NDAA), Trade Agreements Act (TAA)
Packaging content	
Number of cameras	1
Matmenys ir svoris	
Svoris	1,00kg