

Ernitec 0070-08128 security camera IP security camera Indoor & outdoor 2592 x 1944 pixels Ceiling/Pole

Gamintojas: **ERNITEC** · Modelis: **0070-08128** · EAN: **5715328154940** · Prekės kodas: **747839**



2 609,90 €

Kaina su PVM

Be PVM: **2 156,94 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Four 5MP 1/2.8" STARVIS CMOS image sensor
- ✓ 4 adjustable lenses in one camera, each lens up to 5 MP (2592 x 1944) @25/30 fps
- ✓ 2.7 to 13.5 mm motorized lens
- ✓ Smart IR distance up to 40 m
- ✓ True WDR, 3D DNR, ROI, HLC, BLC, Defog
- ✓ Support face, human, vehicle detection and capture
- ✓ Intelligent analytics: intrusion, single line crossing, double line crossing, loitering, wrong-way, illegal parking, enter area, leave area, and smart motion detection and people counting
- ✓ Built-in microphone, 1/1 audio in/out, 4/2 alarm in/out Built-in SD card slot, up to 1TB
- ✓ IP67, IK10
- ✓ 5 Year Warranty



Aprašymas

Saturn-UX-508IR

Wall Mount Bracket Included

Techninė specifikacija

Specifications

Sandėlio grupė > Netzwerk > Netzwerkkamera und Zubehör [+1996][-361]

Performance

Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Alarm input/output	Yes

Design

Mounting type	Ceiling/Pole
Product colour	White
Housing material	Metal
International Protection (IP) code	IP67
IK code	IK10
Weatherproof	Yes

Camera

Lens viewing angle, horizontal	95.6° to 26.9
Lens viewing angle, vertical	65.4° to 20.5

Lens system

Focal length range	2.7 - 13.5 mm
Fixed focus	Yes

Night vision

Night vision	Yes
Night vision distance	40 m
LED type	IR
Infra-red wavelength	850 nm

Video

Maximum resolution	2592 x 1944 pixels
Total megapixels	5 MP
Video intelligence analytic	Yes

Audio

Audio input channels	1.0 channels
Audio output channels	1.0 channels

Built-in microphone	Yes
Network	
Ethernet LAN	Yes
Wi-Fi	No
Storage	
Card reader integrated	Yes
Maximum memory card size	1 TB
Security	
Alarm input channels	4
Alarm output channels	2
Management features	
Reset button	Yes
Power	
Power source type	PoE+
Power consumption (max)	25.3 W
Power over Ethernet (PoE)	Yes
Operational conditions	
Operating temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width	2820 mm
Depth	2820 mm
Height	2063 mm
Weight	4 kg
Packaging data	
Package weight	4.5 kg
Other features	
Warranty period	5 year(s)
Technical details	
Voltage	12 V
Matmenys ir svoris	
Svoris	4,00kg