

TP-Link Omada ES210GP network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) DIN rail Black

Gamintojas: **TP-LINK** · Modelis: **ES210GP** · EAN: **1210002609722** · Prekės kodas: **748624**



116,90 €

Kaina su PVM

Be PVM: **96,61 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 8x Gigabit 802.3af/at-compliant PoE+ RJ45 ports
- ✓ 1x Gigabit RJ45 port, 1x Gigabit SFP/RJ45 Combo port
- ✓ 63W Power Budget, with up to 30W for each PoE port*
- ✓ Easy to Use: Supports plug-and-play for instant connectivity and simple configuration for additional features
- ✓ Centralized Cloud Management via the web or the Omada app†
- ✓ Up to 820ft PoE**, Remote Camera Reboot†, QoS, and Port Isolation for reliable surveillance networking
- ✓ Automatic Loop Prevention, VLAN, and IGMP Snooping
- ✓ Fanless design for silent operation
- ✓ Durable metal casing and desktop/wall mounting design



Aprašymas

TP-Link Omada ES210GP Managed Gigabit PoE+ Switch - 10 Ports (ES210GP)

Techninė specifikacija

Specifications

Sandėlio grupė

> Netzwerk > Switches [+1607][-273]

Management features

Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
Cloud-managed	Yes

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity	10
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Combo SFP ports quantity	1

Network

Networking standards	IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt
10G support	No
Port mirroring	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Auto MDI/MDI-X	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
Auto-negotiation	Yes
VLAN support	Yes
Virtual LAN features	MTU VLAN, Port-based VLAN, Tagged VLAN
Number of VLANs	4000

Optical fiber

Transmission distance (max)	0.25 km
-----------------------------	---------

Data transmission

MAC address table	8000 entries
Switching capacity	20 Gbit/s
Forwarding rate	14.88 Mpps
Store-and-forward	Yes
Jumbo frames support	Yes
Jumbo frames	15000
Packet buffer memory	0.5 MB

Security

DHCP features	DHCP client
IGMP snooping	Yes
Loop protection	Yes
Multicast features	
Multicast support	Yes
Design	
Rack mounting	Yes
Form factor	DIN rail
Product colour	Black
LED indicators	Yes
Power	
Power source	DC
DC input voltage	53 V
Input current	1.31 A
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) type supported	PoE+
Power over Ethernet plus (PoE+) ports quantity	8
Total Power over Ethernet (PoE) budget	63 W
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	209 mm
Depth	126 mm
Height	26 mm
Packaging content	
Cables included	Power
Quick start guide	Yes
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
Matmenys ir svoris	

Matmenys (I × P × A)	32,00cm × 25,00cm × 7,00cm
Svoris	2,40kg