

TP-Link VIGI C340S Kulka (forma) IP apsaugos kamera Lauke 2688 x 1520 pikseliai Siena

Gamintojas: **TP-LINK** · Modelis: **VIGI C340S(4mm)** · EAN: **4895252500790** · Prekės kodas: **748977**



375,90 €

Kaina su PVM

Be PVM: **310,66 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Lauke IP apsaugos kamera
- ✓ CMOS 25,4 / 1,8 mm (1 / 1.8") 4 MP 2688 x 1520 pikseliai
- ✓ Vielinis Ethernet LAN jungtis
- ✓ Naktinis matymas 30 m Balta
- ✓ Kulka (forma) Siena
- ✓ IP67
- ✓ Balta



Aprašymas

VIGI ColorPro Night Vision

VIGI's industry-leading ColorPro Night Vision technology enables its cameras to pierce the night and see everything in fine detail. By adopting this best-in-class technology, VIGI C340S can provide 4MP high resolution and capture more vivid full-color images in extreme low-light conditions.

Better than the Naked Eye

Featuring high low-light sensitivity, VIGI's ColorPro Night Vision produces unparalleled colors along with amazingly crisp images in ultra-low light conditions, which can't be achieved with natural eyesight.

Beyond IR, Beyond Full-Color

Images captured by IR cameras or traditional full-color cameras will suffer from digital noise and the loss of detail. VIGI's ColorPro Night Vision cameras reveal excellent image details even in extreme darkness.

Less Light Pollution

Bright illumination is required by conventional full-color cameras to capture images at pitch-dark hours. But VIGI's ColorPro Night Vision cameras delivers true color and bright imaging even in extremely low light with no spotlights needed, greatly reducing environmental light pollution.

Human & Vehicle Classification

Integrated AI chips support advanced algorithms to distinguish humans and vehicles from other objects. You can flexibly customize alarm rules to match your monitoring needs and receive more accurate event notifications.

Comprehensive AI Detection with Pre-Set Rules Supported

By setting the detection rules in advance, VIGI AI-powered cameras can accurately capture various abnormal events. This will greatly reduce false alarms and cover your specified monitoring needs in different scenarios.

Face Recognition

VIGI's advanced built-in face recognition algorithm enables cameras to intelligently capture faces, extract facial features, and form unique facial data. By comparing the facial data with a face library, quickly match a human face, efficiently reducing the risk of unauthorized access.

People & Vehicle Analytics

Quickly find people and vehicles of interest using a series of attributes.

People Analytics

Filter people of interest by various attributes, such as gender, hair length, and clothing, allowing you to improve search efficiency.

Vehicle Analytics

Identify and search for vehicles of interest based on vehicle color and type for targeting meaningful events in a short time.

Active Defense

Warn potential intruders instantly with sound and light when abnormal events are detected.

Two-Way Audio

With voice intercom support, carry two-way conversations while watching your feed from anywhere.

PoE & IP67

Outdoor PoE connection makes your wiring remarkably easy. Reliable IP67 enables stable outdoor performance.

One system. Full security.

Run your business with peace of mind.

The VIGI professional surveillance system by TP-Link is dedicated to protecting the business you've worked hard to build — whenever, wherever. Our outstanding functions, reliable quality guarantees, and simplified installation work together to ensure your business stays safe and sound.

Techninė specifikacija**Veikimo charakteristikos**

Tipas	IP apsaugos kamera
Talpinimas palaikomas	Lauke
Ryšio technologija	Vielinis
Išplėstinis dinaminis diapazonas (WDR)	Taip
Dienos / nakties režimas	Taip
Šviesos srautas	0,0005 lm
Dinaminis diapazonas	120 dB

Konstrukcija

Montavimo tipas	Siena
Produkto spalva	Balta
Forma	Kulka (forma)
Korpuso medžiaga	Metalas, Plastikas
Tarptautinės apsaugos (IP) kodas	IP67

Fotoaparatas

Minimalus apšviestumas	0,0005 lx
Objektyvo vaizdo kampas, horizontalus	95.2°
Objektyvo vaizdo kampas, vertikalus	50.6°
Objektyvo vaizdo kampas, įstrižainė	114.7°
Posvyrio kampo intervalas	-90 - 90°
Viso diapozonas	-90 - 90°
Kameros užrakto greitis	1/10000 s
Privatumo maskavimo sričių skaičius	4

Vaizdo jutiklis

Jutiklio tipas	CMOS
Optinio sensoriaus dydis	25,4 / 1,8 mm (1 / 1.8")
Progresyvus nuskaitymas	Taip

Lęšių sistema

Lęšių skaičius	1
----------------	---

Aptikties atstumas	70 m
Stebėjimo atstumas	29 m
Atpažinimo atstumas	14 m
Židinio nuotolis	4 mm
Maksimalus apertūros skaičius	1
Identifikavimo atstumas	7 m
Minimalus apertūros skaičius	1
Fiksuotas židinio nuotolis	4 mm
Naktinis matymas	
Naktinis matymas	Taip
Naktinio matymo atstumas	30 m
LED tipas	Balta
Apšvietimo LED diodų skaičius	4
Video	
Maksimali rezoliucija	2688 x 1520 pikseliai
Iš viso megapikselių	4 MP
Video suspaudimo formatai	H.264, H.264+, H.265, H.265+
Palaikomos grafikos rezoliucijos	1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296, 2550 x 1440, 2688 x 1520
Kadrų sparta	60 fps
Triukšmo mažinimas	Taip
Triukšmo sumažinimo technologija	3D triukšmo mažinimas
Privatumo maskavimas	Taip
Bitų sparta	4 Mbps
Tiriamosios srities (ROI) užkodavimas	Taip
Garsas	
Įmontuoti garsiakalbiai	Taip
Bandinių ėmimo dažnis	8 kHz
Signalų ir triukšmo santykis (SNR)	52 dB
Įmontuotas mikrofonas	Taip
Spartos bitais intervalas	64 - 64 Kbit/ai
Tinklas	
Ethernet LAN jungtis	Taip
Eterneto sąsajos tipas	Greitas ethernetas
Palaikomi tinklo protokolai	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS

Ryšys

Ethernet LAN (RJ-45) portų kiekis	1
-----------------------------------	---

Saugumas

Apsauginis slaptažodis	Taip
IP adreso filtravimas	Taip
Privatumo apsauga	Taip
Asimiliuotasis autentifikavimas	Taip

Energijos valdymas

Maitinimo šaltinio tipas	DC
Galios suvartojimas (maks.)	10,1 W
DC išeigos įtampa	12

Aplinkos sąlygos

Darbo temperatūros diapazonas (TT)	-30 - 60 °C
Sandėliavimo temperatūros norma (T-T)	-40 - 60 °C
Darbo santykinės drėgmės diapazonas	0 - 95%
Sandėliavimo santykinis drėgmės diapazonas	0 - 95%

Svoris ir matmenys

Plotis	102 mm
Ilgis	236 mm
Aukštis	99 mm

Pakuotės turinys

Fotoaparatus skaičius	1
-----------------------	---

Matmenys ir svoris

Svoris	0,72kg
--------	--------

Dokumentai ir vaizdo įrašai

- › Naudojimo instrukcija
- › Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbH

Niederkasseler Lohweg 175, 40547 Düsseldorf,
DE
tp-link.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt