

InLine DisplayPort 2.1 cable, UHBR20 80 Gb/s, black, gold-plated contacts, 1m

Gamintojas: **INLINE** · Modelis: **15801P** · EAN: **4043718350742** · Prekės kodas: **749161**



18,90 €

Kaina su PVM

Be PVM: **15,62 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 1 m
- ✓ DisplayPort Straight Male
- ✓ DisplayPort Straight Male
- ✓ DisplayPort version: 2.1
- ✓ 7680 x 2160 pixels 80 Gbit/s
- ✓ Black



Aprašymas

UHBR20 for high-resolution image transmission at up to 80 Gb/s

High transmission performance: DisplayPort 2.1 with UHBR20 transmits data at up to 80 Gb/s and 20 Gb/s per lane.

High resolution and refresh rate: Supports 7680 x 2160 at 240 Hz with 4:4:4 and 10-bit colour depth, as well as 3840 x 2160 at up to 120 Hz with 4:4:4 and 12-bit colour depth.

Secure fit at the connector: The locking mechanism on both DisplayPort plugs protects the connection from accidental disconnection.

High-quality connector: Gold-plated pins and gold-plated connector housings ensure reliable contact quality.

Versatile: The cable is suitable for high-performance monitor connections at workstations, in technical installations and in permanently installed systems.

The DisplayPort 2.1 cable is suitable for high-performance video connections between compatible devices with a DisplayPort connection. It supports

applications with high resolutions and smooth image display. These include high-performance workstations, the display of detailed content and permanently installed monitor set-ups.

The high bandwidth supports demanding video signals. Content with fast-moving images can be displayed on compatible devices with high refresh rates. The locking mechanism on both connectors secures the cable firmly to the port. This is particularly advantageous for permanently installed systems and ports that are difficult to access.

- DisplayPort male to DisplayPort male
- Cable construction: 30 AWG conductor cross-section
- Cable diameter: 7.3 ± 0.2 mm
- Cable sheath: PVC, black
- Kink protection sleeves: PVC, black
- Connector housing: ABS, black
- Connector insulation: blue
- Shielding: AM and braided

Techninė specifikacija

Specifications	
Sandėlio grupė	> Kabel und Adapter > Displayport Kabel und Adapter [+1987][-131]
Features	
Cable length	1 m
Connector 1	DisplayPort
Connector 2	DisplayPort
Connector 1 gender	Male
Connector 2 gender	Male
Maximum resolution	7680 x 2160 pixels
Product colour	Black
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Gold
DisplayPort version	2.1
Supported graphics resolutions	7680 x 4320, 3840 x 2160
Latching connectors	Yes
Magnetically shielded	Yes
Cable shielding	Aluminum mylar foil
Number of shielding layers	3
Jacket material	Polyvinyl chloride (PVC)
Connector housing material	Acrylonitrile butadiene styrene (ABS)
AWG wire size	30
Data transfer rate	80 Gbit/s

Colour sampling	4:4:4
Cable type	Round cable

Weight & dimensions

Cable diameter	7.3 mm
Weight	74 g

Packaging data

Package weight	91 g
Package type	Polybag
Package volume	400 cm ³

Logistics data

Country of origin	China
-------------------	-------

Matmenys ir svoris

Svoris	0,08kg
--------	--------