# InLine DisplayPort 2.1 cable, UHBR20 80 Gb/s, black, gold-plated contacts, 3m

Gamintojas: **INLINE** · Modelis: **15803P** · EAN: **4043718350773** · Prekės kodas: **749163**

**24,90 €**

Kaina su PVM

Be PVM: **20,58 €**

**Sandėlyje**

**Prekė internetu**
Nuskenuokite kodą arba apsilankykite www.shopro.lt

## Pagrindinės savybės

- ✓ 3 m
- ✓ DisplayPort Straight Male
- ✓ DisplayPort Straight Male
- ✓ DisplayPort version: 2.1
- ✓ 7680 x 2160 pixels 80 Gbit/s
- ✓ Black

## Aprašymas

UHBR20 for high-resolution image transmission at up to 80 Gb/s

**High transmission performance:**DisplayPort 2.1 with UHBR20 transmits data at up to 80 Gb/s and 20 Gb/s per lane.
**High resolution and refresh rate:**Supports 7680 x 2160 at 240 Hz with 4:4:4 and 10-bit colour depth, as well as 3840 x 2160 at up to 120 Hz with 4:4:4 and 12-bit colour depth.
**Secure fit at the connector:**The locking mechanism on both DisplayPort plugs protects the connection from accidental disconnection.
**High-quality connector:**Gold-plated pins and gold-plated connector housings ensure reliable contact quality.
**Versatile:**The cable is suitable for high-performance monitor connections at workstations, in technical installations and in permanently installed systems.

The DisplayPort 2.1 cable is suitable for high-performance video connections between compatible devices with a DisplayPort connection. It supports

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

applications with high resolutions and smooth image display. These include high-performance workstations, the display of detailed content and permanently installed monitor set-ups.
The high bandwidth supports demanding video signals. Content with fast-moving images can be displayed on compatible devices with high refresh rates. The locking mechanism on both connectors secures the cable firmly to the port. This is particularly advantageous for permanently installed systems and ports that are difficult to access.

DisplayPort male to DisplayPort male
Cable construction: 30 AWG conductor cross-section
Cable diameter: 7.3 ± 0.2 mm
Cable sheath: PVC, black
Kink protection sleeves: PVC, black
Connector housing: ABS, black
Connector insulation: blue
Shielding: AM and braided

## Techninė specifikacija

| | |
|---|---|
| **Specifications** | |
| Sandėlio grupė | > Kabel und Adapter > Displayport Kabel und Adapter [+1987][-131] |
| **Features** | |
| Cable length | 3 m |
| Connector 1 | DisplayPort |
| Connector 2 | DisplayPort |
| Connector 1 gender | Male |
| Connector 2 gender | Male |
| Maximum resolution | 7680 x 2160 pixels |
| Product colour | Black |
| Connector 1 form factor | Straight |
| Connector 2 form factor | Straight |
| Connector contacts plating | Gold |
| DisplayPort version | 2.1 |
| Supported graphics resolutions | 7680 x 4320, 3840 x 2160 |
| Latching connectors | Yes |
| Magnetically shielded | Yes |
| Cable shielding | Aluminum mylar foil |
| Number of shielding layers | 3 |
| Jacket material | Polyvinyl chloride (PVC) |
| Connector housing material | Acrylonitrile butadiene styrene (ABS) |
| AWG wire size | 30 |
| Data transfer rate | 80 Gbit/s |

| | |
|---|---|
| Colour sampling | 4:4:4 |
| Cable type | Round cable |
| **Weight & dimensions** | |
| Cable diameter | 7.3 mm |
| Weight | 181 g |
| **Packaging data** | |
| Package weight | 193 g |
| Package type | Polybag |
| Package volume | 400 cm³ |
| **Logistics data** | |
| Country of origin | China |
| **Matmenys ir svoris** | |
| Svoris | 0,19kg |