

# Lindy 15m Fibre Optic Hybrid DP 2.0 UHBR10 Cable

Gamintojas: **LINDY** · Modelis: **38521** · EAN: **4002888385213** · Prekės kodas: **749681**



## 172,90 €

Kaina su PVM

Be PVM: **142,89 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ Combines copper and fibre optic cable for a hybrid, long distance DisplayPort connectivity solution
- ✓ Supports resolutions up to 4K@144Hz, 8K@60Hz
- ✓ DP2.0 standard with UHBR10 support, 40Gbps bandwidth (4 lanes, 10Gbps per channel)
- ✓ Flexible and robust cable structure for any kind of installations
- ✓ 2-Year Warranty



## Aprašymas

Lindy's range of Fibre Optic Hybrid cables are a professional solution for extending DP signals over longer distances. Combining the flexibility and high EMI and RFI resistance of fibre optic cable with standard copper cabling, these hybrid cables are ideal for use in critical AV setups, commercial displays or high-performance residential installations.

The internal technology provides uncompressed amplification of the DP signal, allowing long distance extension of DP 8K content that is simply not possible with passive cables.

With 40Gbps bandwidth (UHBR10), these cables support DisplayPort 2.0 resolutions up to 3840x2160@144Hz, and 7680x4320 / 10240x4320@60Hz. Content can be viewed with incredible detail and clarity at higher refresh rates and supporting static and dynamic HDR for optimum viewing of movies, graphics or imagery.

## Techninė specifikacija

| Specifications                 |                                                                   |
|--------------------------------|-------------------------------------------------------------------|
| Sandėlio grupė                 | > Kabel und Adapter > Displayport Kabel und Adapter [+1987][-131] |
| Features                       |                                                                   |
| Cable length                   | 15 m                                                              |
| Connector 1                    | DisplayPort                                                       |
| Connector 2                    | DisplayPort                                                       |
| Connector 1 gender             | Male                                                              |
| Connector 2 gender             | Male                                                              |
| Maximum resolution             | 7680 x 4320 pixels                                                |
| Product colour                 | Black                                                             |
| Connector 1 form factor        | Straight                                                          |
| Connector 2 form factor        | Straight                                                          |
| Connector contacts plating     | Gold                                                              |
| DisplayPort version            | 2                                                                 |
| Supported graphics resolutions | 3840 x 2160, 7680 x 4320                                          |
| Maximum refresh rate           | 60 Hz                                                             |
| Connector 1 lockable           | No                                                                |
| Connector 2 lockable           | No                                                                |
| Jacket material                | Polyvinyl chloride (PVC)                                          |
| Data transfer rate             | 24 Gbit/s                                                         |
| Bandwidth                      | 40 MB/s                                                           |
| Connector material             | Gold                                                              |
| Colour sampling                | 4:2:2, 4:4:4, 4:2:0                                               |
| Cable type                     | Round cable                                                       |
| Operational conditions         |                                                                   |
| Operating temperature (T-T)    | -10 - 60 °C                                                       |
| Storage temperature (T-T)      | -20 - 70 °C                                                       |
| Certificates                   |                                                                   |
| Compliance certificates        | CE, REACH, RoHS, UKCA                                             |
| Weight & dimensions            |                                                                   |
| Bend radius (min)              | 5 cm                                                              |
| Sustainability                 |                                                                   |
| Sustainability compliance      | Yes                                                               |

Matmenys ir svoris

|        |        |
|--------|--------|
| Svoris | 0,50kg |
|--------|--------|