

InLine Gigabit Network Switch 16-Port, 1Gb/s, 19" 1U, fanless

Gamintojas: **INLINE** · Modelis: **323110** · EAN: **4043718298112** · Prekės kodas: **749783**



120,90 €

Kaina su PVM

Be PVM: **99,92 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Basic switching RJ-45 Ethernet ports quantity: 16
- ✓ Cat3, Cat4, Cat5, Cat5e 10BASE-T, 100BASE-TX, 1000BASE-T
- ✓ MAC address table: 8000 entries Switching capacity: 32 Gbit/s
- ✓ 1U Rack mounting
- ✓ AC Power supply included



Aprašymas

16-port gigabit switch for reliable network expansion with 1 Gb/s per port with **auto-negotiation**

Plug & Play and Auto MDI/MDI-X crossover detection – Each individual port automatically detects the speed of the connected devices

Green IT: Energy-saving thanks to IEEE 802.3az Energy Efficient Ethernet through cable length detection and automatic signal strength

Store-and-forward switching to avoid corrupted packets

Freightless 19" 1U housing for low noise operation

The InLine® 16-port Gigabit network switch is a powerful and uncomplicated solution for expanding existing network infrastructures. Each of the sixteen RJ45 ports automatically detects the speed of the connected devices (10/100/1000 Mb/s) and adapts flexibly in half or full duplex mode. Thanks to Auto-MDI/MDI-X, the type of network cable used is irrelevant. The store-and-forward technology ensures efficient forwarding of data packets and prevents the transmission of faulty data. With IEEE 802.3az Energy Efficient Ethernet (EEE), cable lengths and network activities are detected to dynamically reduce energy consumption - ideal for sustainable IT environments.

The switch is designed to be fanless and therefore quiet in operation, perfect for office, laboratory or server rack environments. The 19-inch rack

mounting in 1U enables easy integration into existing structures.

Technical specifications:

16x RJ45 ports, 10/100/1000Base-T, Auto-MDI/MDI-X
Chipsätze: RTL8382L + RTL8218D + 2x RTL8231
Standards: IEEE 802.3, 802.3u, 802.3ab, 802.3x, 802.3az
Store-and-forward switching
MAC address table: 8K, auto-learning & auto-update
Jumbo frame: 9216 bytes
Bandwidth: 32 Gbit/s
LED indicators: PWR, LNK/ACT
Network cable: Cat. 5/5e or higher (up to 100 m)
Dimensions: 480 x 180 x 44 mm
Weight: approx. 2.15 kg
Power supply: 100-240V AC, 50/60 Hz
Max. Power consumption: 21 W
Operating temperature: 0-40 °C
Storage temperature: -40-70 °C
Humidity: operation 10-90 %, storage 5-90 % (non-condensing)

Scope of delivery:

1x InLine® PoE+ Gigabit network injector hub 8 port
2x operating instructions (German/English)
1x power supply
2x 19" mounting bracket
6x screws for the mounting brackets
4x rubber feet

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	16
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Gigabit Ethernet (copper) ports quantity	16
Power connector	AC-in jack
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T

Cable types supported	Cat3, Cat4, Cat5, Cat5e
Auto MDI/MDI-X	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
Data transmission	
MAC address table	8000 entries
Switching capacity	32 Gbit/s
Store-and-forward	Yes
Jumbo frames support	Yes
Jumbo frames	9216
Design	
Rack mounting	Yes
Form factor	1U
Product colour	Black
Housing material	Metal
LED indicators	Activity, Link, Power
Performance	
Built-in processor	Yes
Maximum data transfer rate	1000 Mbit/s
Fanless	Yes
Power	
Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (max)	21 W
Other features	
Dimensions (WxDxH)	440 x 24.39 x 180 mm
Ethernet interface type	Fast Ethernet, Gigabit Ethernet
Ethernet LAN (RJ-45) ports	16
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions

Width	440 mm
Depth	24.4 mm
Height	180 mm
Weight	4.7 kg

Packaging content

Cables included	AC
Rack mount kit	Yes

Packaging data

Package type	Box
Package width	260 mm
Package depth	520 mm
Package height	110 mm
Package weight	1.76 kg

Matmenys ir svoris

Svoris	2,44kg
--------	--------