

Bosch MIC IP starlight 7100i IP security camera Indoor & outdoor Ceiling

Gamintojas: **BOSCH** · Modelis: **MIC-7522-Z30W** · EAN: **4060039034946** · Prekės kodas: **749796**



7 806,90 €

Kaina su PVM

Be PVM: **6 451,98 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Starlight camera technology with excellent low-light sensitivity (color = 0.0047 lx) and High dynamic range (120 dB) (to see details in bright and dark areas simultaneously)
- ✓ Exceptional strength and ruggedness for any outdoor application including traffic monitoring (bridges, tunnels, or highways), perimeter protection, city surveillance, and mining
- ✓ Built-in Camera Trainer to train the camera to recognize user-specified target objects, such as moving and non-moving objects, to alert operators of unusual scene activity
- ✓ Edge intelligence with Intelligent Tracking and object detection even when the camera is moving
- ✓ Optional illuminator with multispectral LEDs that distribute IR light uniformly in the field (up to 550 m (1804.50 ft)) to avoid dark spots or an over-illuminated scene

Aprašymas

Bosch MIC IP Starlight 7100i Innen & Außen Zimmerdecke (MIC-7522-Z30W)

Techninė specifikacija

Specifications

Sandėlio grupė > Netzwerk > Netzwerkkamera und Zubehör [+1996][-361]

Performance

Type IP security camera

Placement supported Indoor & outdoor

Connectivity technology	Wired
Design	
Mounting type	Ceiling
Product colour	White
Housing material	Aluminium
Protection features	Impact resistant
International Protection (IP) code	IP66, IP68
Camera	
Minimum illumination	0.0047 lx
Pan range	0 - 360°
Lens system	
Zoom capability	Yes
Optical zoom	12x
Focal length range	6.6 - 198 mm
Maximum aperture number	4.8
Minimum aperture number	1.5
Video	
Total megapixels	2 MP
Video compression formats	H.264, M-JPEG, H.265, HEVC
Supported graphics resolutions	1920 x 1080 (HD 1080), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 704 x 480, 768 x 432, 512 x 288, 256 x 144, 640 x 480 (VGA)
Noise reduction	Yes
Network	
Ethernet LAN	Yes
Storage	
Card reader integrated	Yes
Compatible memory cards	SD
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
RS-485 ports	1
Management features	
Web browser	Yes
Power	
Power source type	AC, PoE

AC input voltage	24 V
------------------	------

Operational conditions

Operating temperature (T-T)	-40 - 65 °C
-----------------------------	-------------

Storage temperature (T-T)	-40 - 70 °C
---------------------------	-------------

Weight & dimensions

Weight	8.7 kg
--------	--------

Packaging content

Number of cameras	1
-------------------	---

Matmenys ir svoris

Svoris	1,00kg
--------	--------