

InLine PoE+ Gigabit Injector Hub 16 Port PoE+, 19"1U, brackets included, 2 fans

Gamintojas: **INLINE** · Modelis: **32316H** · EAN: **4043718288748** · Prekės kodas: **749802**



276,90 €

Kaina su PVM

Be PVM: **228,84 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 10,100,1000 Mbit/s
- ✓ Power over Ethernet (PoE) IEEE 802.3ab, IEEE 802.3af, IEEE 802.3u
- ✓ Auto MDI/MDI-X
- ✓ Black



Aprašymas

The InLine® PoE+ Gigabit Network Injector Hub is a fast and flexible solution for upgrading the existing network to Power over Ethernet according to IEEE 802.3af / IEEE 802.3at without replacing existing switches. The injector hub provides triple protection against overcurrent, overvoltage and overheating at each port. In addition, the Injector Hub offers both IEEE 802.3af PoE and IEEE 802.3at PoE+ with up to 30 watts of power per port via a single Cat. 5 / 5e / 6 Ethernet cable with a combined total power of 250 watts. Sixteen 10/100/1000Mbit/s PoE+ ports solve the problem of a limited number of available sockets and offer system administrators a flexible solution for operating the network device to be supplied with power, such as PoE-capable IP cameras or wireless access points, almost everywhere.

Technical characteristics

Standards: IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T, IEEE 802.3af Power over Ethernet, IEEE 802.3at Power over Ethernet Plus

Ports "DATA IN": 16x 10/100/1000Base-T RJ45, Auto-MDI/MDI-X

Ports "DATA + PWR OUT": 16x 10/100/1000Base-T RJ45, Auto-MDI/MDI-X

PoE type of power supply: Endspan

PoE output voltage: Per port 48~56V DC

PoE output power: Per Port max. 30 watts

Power pin assignment: 1/2(+), 3/6(-)

Total power: 250 watts

LED indicators: PWR, PoE (1-16)

Dimensions (W x D x H): 358x205x44mm

Weight: appr. 2.4 kg

Power requirement: 100~240V AC external power adapter

Operating environment: Operating temperature 0-40°C, storage temperature -10-70°C, humidity 20-95% non-condensing

Content of delivery

1x InLine® PoE+ Gigabit Network Injector Hub 16 Port

2x User manual (German/English)

1x Power supply

2x 19" mounting brackets

6x Screws for the mounting brackets

4x Rubber feet

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Network	
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Power over Ethernet (PoE)	Yes
Networking standards	IEEE 802.3ab, IEEE 802.3af, IEEE 802.3u
Auto MDI/MDI-X	Yes
Features	
Product colour	Black
Power protection features	Over current, Over voltage, Overheating
Ports & interfaces	
Ethernet LAN (RJ-45) ports	16
RJ-45 input ports	16
RJ-45 output ports	16
Power	
Power over Ethernet (PoE) voltage	56 V
Output power	250 W
AC adapter input voltage	100 - 240 V

Power over Ethernet (PoE) power per port	30 W
--	------

Certificates

Compliance industry standards	IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T, IEEE 802.3af Power over Ethernet, IEEE 802.3at Power over Ethernet Plus
-------------------------------	---

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 95%
Storage temperature (T-T)	-10 - 70 °C

Weight & dimensions

Size (imperial)	48.3 cm (19")
Width	200 mm
Depth	358 mm
Height	43 mm
Weight	45384 kg
Dimensions (WxDxH)	200 x 358 x 43 mm

Packaging content

Wall mounting kit	Yes
AC adapter included	Yes
Power cord included	Yes
Manual	Yes

Packaging data

Package width	260 mm
Package depth	535 mm
Package height	950 mm
Package weight	3.3 kg

Matmenys ir svoris

Svoris	3,30kg
--------	--------