

Ernitec 0070-08117-V2 security camera IP security camera Indoor & outdoor 2592 x 1944 pixels Ceiling/Wall/Pole

Gamintojas: **ERNITEC** · Modelis: **0070-08117-V2** · EAN: **5715328164048** · Prekės kodas: **750100**



346,89 €

Kaina su PVM

Be PVM: **286,69 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 1/2.8" Progressive scan CMOS
- ✓ 2592×1944 @ 25/30fps (5MP)
- ✓ 2.7-13.5mm Motorized lens
- ✓ Smart IR up to 40m
- ✓ WDR, 3D DNR, ROI, HLC, BLC, Defog
- ✓ Support face, human, vehicle detection and capture
- ✓ 1/1 audio in/out, 1/1 alarm in/out
- ✓ Power Supply DC12V / POE (IEEE 802.3af)
- ✓ IP66, IK10
- ✓ 5 Year Warranty

Aprašymas

Pluto-PX-325IR

The Ernitec Vandalproof IP Dome Camera combines advanced technology with robust design, making it an ideal choice for comprehensive surveillance solutions.

Techninė specifikacija

Specifications

Sandėlio grupė

> Netzwerk > Netzwerkkamera und Zubehör [+1996][+361]

Performance

Type

IP security camera

Placement supported

Indoor & outdoor

Connectivity technology	Wired
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Alarm input/output	Yes

Design

Mounting type	Ceiling/Wall/Pole
Product colour	White
Housing material	Metal
International Protection (IP) code	IP66
IK code	IK10
Weatherproof	Yes

Camera

Camera pan control	No
Minimum illumination	0.03 lx
Lens viewing angle, horizontal	87.5-26°
Lens viewing angle, vertical	64.8-19.9°
White balance	Auto

Image sensor

Sensor type	CMOS
-------------	------

Lens system

Focal length range	2.7 - 13.5 mm
--------------------	---------------

Night vision

Night vision	Yes
Night vision distance	40 m
LED type	IR
Infra-red wavelength	850 nm

Video

Maximum resolution	2592 x 1944 pixels
Total megapixels	5 MP
Video intelligence analytic	Yes
Back Light Compensation (BLC)	Yes

Audio

Audio input channels	1.0 channels
Audio output channels	1.0 channels

Built-in microphone	Yes
Network	
Ethernet LAN	Yes
Wi-Fi	No
Storage	
Card reader integrated	Yes
Maximum memory card size	256 GB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Security	
Alarm input channels	1
Alarm output channels	1
Management features	
Web-based management	Yes
Web browser	Yes
Firmware upgradeable	Yes
Remotely operated	Yes
Power	
Power source type	PoE
Power consumption (max)	7.5 W
Power over Ethernet (PoE)	Yes
Operational conditions	
Operating relative humidity (H-H)	0 - 95%
Weight & dimensions	
Weight	730 g
Packaging data	
Package weight	1 kg
Other features	
Dimensions (WxDxH)	140 x 140 x 109 mm
Warranty period	5 year(s)
Matmenys ir svoris	
Svoris	0,73kg