

TP-Link Omada ES224G network switch Managed L2 Gigabit Ethernet (10/100/1000) Black

Gamintojas: **TP-LINK** · Modelis: **ES224G** · EAN: **1210002600705** · Prekės kodas: **750114**



124,90 €

Kaina su PVM

Be PVM: **103,22 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 24× 10/100/1000Mbps RJ45 ports
- ✓ Easy to Use: Supports plug-and-play for instant connectivity and simple configuration for additional features
- ✓ Centralized Cloud Management via the web or the Omada app
- ✓ VLAN, Port Isolation, Cable Test, QoS for reliable surveillance networking
- ✓ Automatic Loop Prevention and IGMP Snooping
- ✓ Fanless design for silent operation
- ✓ Durable metal casing and desktop/rack mounting design



Aprašymas

Omada Cloud Essentials — A Free and Easy Cloud-Based Network Management

Omada Cloud Essentials is a free, easy-to-use version of the Omada Cloud-based Controller. It provides cloud-based centralized management and monitoring for the Omada networking system, covering access points, switches, and gateways, ideal for surveillance networks and small businesses.

Techninė specifikacija

Specifications	
Sandėlio grupė	> Netzwerk > Switches [+1607][-273]
Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
Cloud-managed	Yes
Unified static configuration	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	24
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Gigabit Ethernet (copper) ports quantity	24
Network	
Port mirroring	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Fast leave	Yes
VLAN support	Yes
Virtual LAN features	MTU VLAN, Port-based VLAN
Number of VLANs	32
Data transmission	
MAC address table	8000 entries
Switching capacity	48 Gbit/s
Forwarding rate	35.7 Mpps
Store-and-forward	Yes
Jumbo frames support	Yes
Jumbo frames	15000
Packet buffer memory	4 MB

Security

DHCP features	DHCP client
IGMP snooping	Yes
Queue scheduling algorithms	Weighted Round Robin (WRR)

Multicast features

Multicast support	Yes
-------------------	-----

Design

Rack mounting	Yes
Product colour	Black

Performance

Firmware upgradeable	Yes
Fanless	Yes

Power

Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Surge protection	Yes
Surge protection voltage	6 kV

Operational conditions

Operating temperature (T-T)	-5 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions

Width	294 mm
Depth	140 mm
Height	44 mm

Packaging content

Cables included	AC
User guide	Yes
Rack mount kit	No

Certificates

Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
-------------------------	---

Matmenys ir svoris

Matmenys (I × P × A)	35,00cm × 24,00cm × 8,00cm
----------------------	----------------------------

Svoris	1,91kg
--------	--------