

Bosch FLEXIDOME panoramic 5100i Bullet IP security camera Indoor & outdoor 1920 x 1080 pixels Ceiling

Gamintojas: **BOSCH** · Modelis: **NDS-5703-F360** · EAN: **4060039112118** · Prekės kodas: **750946**



1 034,90 €

Kaina su PVM

Be PVM: **855,29 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 360° panoramic overview in 6MP resolution without blind spots
- ✓ High Dynamic Range to see every detail in both bright and dark areas of the scene
- ✓ Edge or client-side dewarping for easy integration and flexible viewing and recording
- ✓ Built-in IVA Pro Buildings, IVA Pro Perimeter and Intelligent Audio Analytics to trigger relevant alerts and quickly retrieve data
- ✓ Compact design for unobtrusive indoor use with quick and easy installation and set-up

Aprašymas

Fixed dome 6MP 360° (NDS-5703-F360)

Techninė specifikacija

Specifications

Sandėlio grupė

> Netzwerk > Netzwerkkamera und Zubehör [+1996][-361]

Performance

Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
Day/night mode	Yes

Infrared (IR) cut-off filter	Yes
Alarm input/output	Yes
Design	
Mounting type	Ceiling
Product colour	White
Form factor	Bullet
Protection features	Impact resistant
International Protection (IP) code	IP66
Country of origin	Thailand
Camera	
Camera pan control	Yes
Pan range	0 - 355°
White balance	Auto, Manual
Camera shutter type	Electronic
Camera shutter speed	1/1.875 to 1/150000
Number of Privacy masking areas	8
Image sensor	
Sensor type	CMOS
Number of sensors	1
Optical sensor size	25.4 / 1.8 mm (1 / 1.8")
Number of effective pixels (H x V)	2.112 x 2.112 pixels
Panoramic camera	
Signal-to-Noise Ratio (SNR) (panoramic camera)	50 dB
Lens system	
Number of lenses	1
Focus	Motorized
Night vision	
Night vision	Yes
Video	
Maximum resolution	1920 x 1080 pixels
Total megapixels	6 MP
Video compression formats	H.264, M-JPEG, H.265, HEVC
Frame rate	30 fps
Image quality adjustment	Brightness, Saturation, Sharpness

Back Light Compensation (BLC)	Yes
Audio	
Audio system full duplex	Yes
Built-in microphone	Yes
Voice codecs	AAC, G.711
Network	
Ethernet LAN	Yes
Ethernet interface type	Gigabit Ethernet
Supported network protocols	IPv4; IPv6; UDP; TCP; HTTP; HTTPS; RTP/RTCP; IGMP V2/V3; ICMP; ICMPv6; RTSP; FTP; ARP; DHCP; APIPA (Auto-IP, link local address); NTP (SNTP); SNMP (V1, MIBII); SNMP (V3, MIBII); 802.1x, EAP/ TLS; DNS; DNSv6; DDNS (DynDNS.org, selfHOST.de, noip.com); SMTP; iSCSI; UPnP (SSDP); DiffServ (QoS); LLDP; SOAP; CHAP; Digest authentication
Quality of Service (QoS) support	Yes
Storage	
Compatible memory cards	SD, SDHC, SDXC
RAM capacity	2.048 MB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
HDMI ports quantity	1
Security	
Temperature sensor	Yes
Pixel counter	Yes
Management features	
Behavior analysis	Line crossing detection
Power	
Power source type	PoE
Power consumption (Power over Ethernet (PoE))	6 W
Operational conditions	
Operating temperature (T-T)	-10 - 45 °C
Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	0 - 98%
Weight & dimensions	
Height	47.7 mm
Diameter	11 cm
Weight	310 g

Packaging content

Number of cameras	12
-------------------	----

Matmenys ir svoris

Svoris	1,00kg
--------	--------