

Cudy LT500E wireless router Fast Ethernet Dual-band (2.4 GHz / 5 GHz) 4G White

Gamintojas: **CUDY** · Modelis: **LT500E** · EAN: **6971690791896** · Prekės kodas: **751867**



53,91 €

Kaina su PVM

Be PVM: **44,55 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 4G Cat. 4 with Max 150 Mbps DL
- ✓ 4-Stream Dual-Band Wi-Fi 5
- ✓ 867 Mbps + 300 Mbps Wi-Fi
- ✓ 4x Fast Ethernet Ports
- ✓ 1x Nano SIM Slot
- ✓ Cudy Mesh, VPN Server and Client
- ✓ Cudy App, Cloud Control



Aprašymas

Turn 4G into Internet for All

Share via Speedy AC1200 Wi-Fi

Dual-band WiFi allows newer devices to stream on the less congested 5 GHz band, while IoT and legacy devices can connect to the 2.4 GHz band, making your video chatting, 4K playback and light control feel as smooth as possible.

Share via Fast Ethernet

Share a stable wired connection for TV and PC. The LAN/WAN port can be configured as a WAN port, connecting to another ISP and enabling WAN failover if the SIM card is inserted in.

Easy Setup and Versatile Management

Easy to Use and Move

Insert your Nano SIM card and power up to get network instantly. No rigid subscription, nor complex wiring.

Network Redundancy

Set up the backup to make sure your surveillance and the rest stay connected even when WAN/WISP is down.

Client Management

Set a bedtime and a domain blacklist to regulate your children's online behaviour.

VPN Client and Server

Connect to VPN with WireGuard/OpenVPN/Zerotier/PPTP/L2TP protocols or host your own server at home/office.

Plug in a SIM Card to Enjoy the Network

Home

Plug and play easy-to-install WiFi for every home—no rigid broadband subscription is required.

Automobile

Provide decent networks for all devices on your road journey.

Surveillance

Make sure the network is always on with the WAN + WISP + 4G backup function.

Booth

Utilized the flexible pay-as-you-go plan to equip your temporary booth with a fast network. (SIM card is not included)

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Access Points/Routers [+1554][–541]
WAN connection	
Ethernet WAN	Yes
DSL WAN	No
SIM card slot	Yes
3G/4G USB modem compatibility	No
WAN connection type	RJ-45
Wireless LAN features	
Wi-Fi band	Dual-band (2.4 GHz / 5 GHz)
Top Wi-Fi standard	Wi-Fi 5 (802.11ac)
WLAN data transfer rate (max)	867 Mbit/s
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
WLAN data transfer rate (first band)	300 Mbit/s

WLAN data transfer rate (second band)	867 Mbit/s
Modulation	256-QAM
Network	
Ethernet LAN	Yes
Ethernet LAN interface type	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Port forwarding	Yes
Port triggering	Yes
Dynamic DNS (DDNS)	Yes
Number of guest networks (2.4 GHz)	1
Number of guest networks (5 GHz)	1
VPN server	WireGuard OpenVPN IPsec ZeroTier PPTP L2TP
Mobile network	
Mobile network generation	4G
3G standards	WCDMA
4G standard	LTE-TDD & LTE-FDD
SIM card type	NanoSIM
Ports & interfaces	
Ethernet LAN (RJ-45) ports	4
USB port	No
DC-in jack	Yes
Management features	
Web-based management	Yes
Quality of Service (QoS) support	Yes
Wake-on-LAN ready	Yes
Reset button	Yes
WPS push button	Yes
MU-MIMO technology	Yes
MIMO	Yes
Security	
Security algorithms	WPA, WPA2, WPA3
Firewall	Yes
Guest access	Yes
Filtering	Yes

MAC address filtering	Yes
IP address filtering	Yes
URL filtering	Yes
IGMP snooping	Yes
DMZ support	Yes
Protocols	
DHCP client	Yes
DHCP server	Yes
Design	
Product type	Desktop/pole router
Product colour	White
LED indicators	LAN, LTE, Link, System, WAN, WLAN, WPS
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC)
Packaging content	
Cables included	LAN (RJ-45)
AC adapter included	Yes
Quick installation guide	Yes
Antenna	
Antenna design	Internal
Antenna type	2x2
Antenna gain level (max)	3.97 dBi
Antennas quantity	4
Features	
Built-in processor	Yes
Processor frequency	580 MHz
Processor cores	1
Internal memory	128 MB
Flash memory	16 MB
Power	
Power source type	DC
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Output voltage	12 V

Output current	1 A
----------------	-----

Operational conditions

Operating temperature (T-T)	0 - 40 °C
-----------------------------	-----------

Storage temperature (T-T)	-40 - 70 °C
---------------------------	-------------

Operating relative humidity (H-H)	10 - 90%
-----------------------------------	----------

Storage relative humidity (H-H)	5 - 90%
---------------------------------	---------

Weight & dimensions

Width	190 mm
-------	--------

Depth	148.8 mm
-------	----------

Height	50 mm
--------	-------

Weight	300 g
--------	-------

Packaging data

Package width	270 mm
---------------	--------

Package depth	168 mm
---------------	--------

Package height	58 mm
----------------	-------

Package weight	600 g
----------------	-------

Matmenys ir svoris

Matmenys (l × p × A)	6,00cm × 27,00cm × 17,00cm
----------------------	----------------------------