

Zyxel WAX610D-EU0101F wireless access point 2400 Mbit/s White Power over Ethernet (PoE)

Gamintojas: ZYXEL · Modelis: WAX610D-EU0101F · EAN: 4718937612970 · Prekės kodas: 751915



394,90 €

Kaina su PVM

Be PVM: 326,36 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 2.4 GHz 575 Mbit/s
- ✓ 5 GHz 2400 Mbit/s
- ✓ Maximum data transfer rate: 2400 Mbit/s
- ✓ IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
- ✓ EAP, WEP, WPA, WPA2
- ✓ Power over Ethernet (PoE)
- ✓ Internal



Aprašymas

True WiFi 6 experience for all

The WAX610D is designed to deliver the true WiFi 6 experience to users for various types of applications. Featuring 6 spatial streams (4x4:4 in 5GHz, 2x2:2 in 2.4GHz), OFDMA and MU-MIMO capabilities, the WAX610D can provide fabulous efficiency for your wireless networking.

An access point that fits your need

We understand that mounting an access point to the ceiling isn't always possible due to the challenging environments like warehouses, historical

buildings or stylish hotels where the aesthetics of the building are a priority. The WAX610D is equipped with a dual-optimized antenna that is selectable, allowing the access point to be mounted on the wall or on the ceiling without compromising on performance and coverage.

Hassle-free upgrade

To meet the growing demands for WiFi connectivity, the WAX610D enhances the network capacity with 2.90 Gbps WiFi speed and 2.5 Gbps multi-gigabit Ethernet port, which allows multi-gigabit speed run on the existing infrastructure without the need of re-cabling. The WAX610D enables organizations such as schools, hotels, and retail stores to upgrade to the latest WiFi 6 technology easily without breaking the bank.

Manage it your way!

The WAX610D comes with the support of NebulaFlex Pro, which offers the full flexibility for users to easily switch between cloud-managed, controller-managed, and standalone modes. You can choose the appropriate managed-mode best suited for your needs.

Techninė specifikacija

Specifications	
Sandėlio grupė	Server, Storage & Network > Access Points/Routers [+1554][-541]
Features	
2.4 GHz	Yes
5 GHz	Yes
Maximum data transfer rate	2400 Mbit/s
Maximum data transfer rate (2.4 GHz)	575 Mbit/s
Maximum data transfer rate (5 GHz)	2400 Mbit/s
Ethernet LAN data rates	10,100,1000,2500 Mbit/s
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
MIMO	Yes
MIMO type	Multi User MIMO
VLAN support	Yes
Security	
Security algorithms	EAP, WEP, WPA, WPA2
MAC address filtering	Yes
Remote Authentication Dial-In User Service (RADIUS)	Yes
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
DC-in jack	Yes
Power	
Power over Ethernet (PoE)	Yes
AC input voltage	12 V

Design

Placement	Wall
Product colour	White

Antenna

Antenna type	Internal
--------------	----------

Weight & dimensions

Width	229 mm
Depth	216 mm
Height	64 mm
Weight	780 g

Packaging content

Quantity per pack	1 pc(s)
-------------------	---------

Operational conditions

Operating relative humidity (H-H)	10 - 95%
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-30 - 70 °C
Storage relative humidity (H-H)	10 - 90%

Logistics data

Harmonized System (HS) code	85176990
-----------------------------	----------