

TP-Link HX141 Dual-band (2.4 GHz / 5 GHz) Wi-Fi 6 (802.11ax) White 3 Internal

Gamintojas: **TP-LINK** · Modelis: **HX141(1-PACK)** · EAN: **4895252503906** · Prekės kodas: **756059**



83,90 €

Kaina su PVM

Be PVM: **69,34 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Dual Band WiFi: Speeds up to 1500 Mbps—1201 Mbps on 5 GHz and 300 Mbps on 2.4 GHz
- ✓ Connect More, Stay Fast: Equipped with the WiFi 6 wireless technology for faster speeds, greater capacity, and reduced network congestion.*
- ✓ Boosted Coverage: High-performance antennas and beamforming technology combine to extend strong, reliable WiFi signals
- ✓ EasyMesh Compatible: Create a unified smart mesh network with seamless coverage and greater flexibility based on standard mesh technology.**
- ✓ One Unified Network: Multiple units form a whole-home network that auto-selects the best connection as you move around your home
- ✓ Gigabit Wired Speeds: 1× Gigabit WAN/LAN port and 2× Gigabit LAN ports offer flexible and fast internet access
- ✓ Enhanced Security: WPA3 encryption, Multi-SSID, and parental controls provide personalized and safer online experience.*
- ✓ Easy Setup and Use: Set up your mesh WiFi in minutes with powerful Aginet app
- ✓ Remote Management: TR-069, TR-181, TR-111, and TR-143 are supported



Techninė specifikacija

Specifications

Sandėlio grupė Server, Storage & Network > Access Points/Routers [+1554][-541]

Design

Product colour	White
Antenna type	Internal
Product type	Mesh router
LED indicators	Yes
Reset button	Yes

Wireless LAN features

Wi-Fi band	Dual-band (2.4 GHz / 5 GHz)
Top Wi-Fi standard	Wi-Fi 6 (802.11ax)
WLAN data transfer rate (max)	1500 Mbit/s
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)
WLAN data transfer rate (first band)	574 Mbit/s
WLAN data transfer rate (second band)	1201 Mbit/s
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g
Security algorithms	WMM, WPA, WPA2, WPA3
Point-to-point protocol over Ethernet (PPPoE)	Yes
Dynamic IP	Yes
Static IP	Yes

Features

Quality of Service (QoS) support	Yes
Port forwarding	Yes
Firewall security	SPI Firewall
Transmitting power (CE)	20 - 23 dBm
Transmitting power (FCC)	30 dBm
Mobile operating systems supported	Android 4.4, iOS 9.0
Parental control	Yes
SSID Broadcast	Yes
MU-MIMO technology	Yes

Ports & interfaces

Ethernet LAN (RJ-45) ports	3
Ethernet WAN	Yes
DC-in jack	Yes

Power

AC input voltage	12 V
AC adapter input current	1 A

Certificates

Compliance certificates	CE
Certification	CE

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions

Width	100 mm
Depth	100 mm
Height	89.5 mm

Packaging content

Number of products included	1 pc(s)
AC adapter included	Yes
Number of units included	1 pc(s)
Ethernet cable	Yes
Quick installation guide	Yes