

Uni-T UT203R Digital Clamp Meter

Gamintojas: **UNI-T** · Modelis: **UT203R** · EAN: **6935750520390** · Prekės kodas: **759165**



72,90 €

Kaina su PVM

Be PVM: **60,25 €**

Sandėlyje



Prekė internetu

Nuskuokite kodą arba apsilankykite www.shopro.lt



Aprašymas

Uni-T UT203R Digital Clamp Meter

The Uni-T UT203R universal clamp meter is a practical tool for everyday electrical measurements. It is ideal for inspecting installations, diagnosing basic circuits, and measuring current without having to open the circuit. Thanks to its clamp design, it allows for convenient and quick measurements in the field.

AC and DC Current Measurement

The UT203R model allows for the measurement of AC and DC current up to 400 A and AC and DC voltage up to 600 V, making it more versatile for everyday use. Additionally, it offers capacitance and frequency measurement, which expands its applications in diagnosing various devices.

User-friendly features

The multimeter is equipped with True RMS, NCV, diode test, continuity test, Data Hold, and Relative mode. The zeroing function for DC measurement makes working with direct current measurements more convenient and improves user comfort.

Clear design and safe operation

The large backlit screen makes it easy to read results, and the 28 mm jaw opening allows for a comfortable grip on the wire during measurement. Compliance with safety categories CAT II 600V and CAT III 300V allows the device to be used in typical electrical applications.

Included

- Clamp meter
- Batteries x2
- Test leads
- User manual

Specifications

Manufacturer	Uni-T
Model	UT203R
Type	Clamp meter
AC current	0.04~400A ±(2%+5)
DC current	0.04~400A ±(2%+5)
AC Voltage	600V ±(0.8%+5)
AC Voltage Frequency	10Hz~60kHz ±(0.5%+2)
DC Voltage	600V ±(0.5%+2)
Resistance	40MΩ
Capacitance	40mF ±(4%+5)
Frequency	10Hz~10MHz ±(0.1%+4)
Maximum reading	4000
Functions	True RMS, NCV, diode test, continuity test, Data Hold, Relative mode, LCD backlight
Jaw opening	28 mm
Power supply	2x 1.5V battery (R03)
Safety	CAT II 600V / CAT III 300V
Dimensions	215 x 63 x 36 mm
Certifications	CE, UKCA, cETLus

GPSR Link: https://psr-assets.innpro.pl/tools/sg_tools_measuring_tools.pdf, Gross weight: 420, Net weight: 235, Box length: 23,00, Box width: 8,50, Box height: 5,50

Techninė specifikacija

Specifications	
Sandėlio grupė	Tools/Measuring tools [+119][-130]
Matmenys ir svoris	
Matmenys (I × P × A)	23,00cm × 8,00cm × 5,00cm
Svoris	0,42kg