

Review of the Uni-T RCD UT582+

Gamintojas: **UNI-T** · Modelis: **UT582+** · EAN: **6935750558218** · Prekės kodas: **759173**



123,90 €

Kaina su PVM

Be PVM: **102,40 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Uni-T RCD tester UT582+

The Uni-T UT582+ tester is a device designed to test the operation of residual current devices (RCDs) in single-phase installations. It allows you to verify whether the protective devices respond correctly, which is essential during electrical system inspections and maintenance work.

Accurate RCD testing

The UT582+ model allows for the measurement of trip time and trip current for various rated values, enabling the assessment of the proper operation of the protective devices. The AUTO RAMP function facilitates automatic verification of the trip threshold, and the device also offers voltage measurement up to 600V.

Features for convenience and safety

The device is equipped with a backlit display, a Data Hold function, and audible signals indicating errors and operating status. Fuse protection and connection indicators enhance safety, while automatic shutdown helps save energy.

Included

- RCD tester

- Test leads (1 pair)
- 6 AA batteries (LR6)
- Carrying case
- Wrist strap
- User manual

Specifications

Manufacturer	Uni-T
Model	UT582+
Product type	RCD tester
Operating voltage range	195-253 V
Voltage measurement range	30-600 V $\pm(3\% + 3)$
Frequency range	45-65 Hz
Test currents	10 mA / 20 mA / 30 mA / 100 mA / 300 mA / 500 mA
Response time range	40-2000 ms
Response time accuracy	$\pm(2\% + 2)$
Maximum display reading	999
Functions	AUTO RAMP, Data Hold, LCD backlight, audible alarm, connection check, auto power off, low battery indicator
Power supply	6 $\times$ 1.5 V AA batteries (LR6)
Display dimensions	71 $\times$ 34 mm
Dimensions	160 $\times$ 100 $\times$ 71 mm
Weight	400 g
Certifications	CE, UKCA

GPSR Link: https://psr-assets.innpro.pl/tools/sg_tools_measuring_tools.pdf, Gross weight: 1060, Net weight: 400, Box length: 20,50, Box width: 15,00, Box height: 8,00

Techninė specifikacija

Matmenys ir svoris	
Matmenys (I $\times$ P $\times$ A)	20,00cm $\times$ 15,00cm $\times$ 8,00cm
Svoris	1,06kg