

Uni-T UT315A Vibration Tester

Gamintojas: **UNI-T** · Modelis: **UT315A** · EAN: **6935750531518** · Prekės kodas: **759192**



340,91 €

Kaina su PVM

Be PVM: **281,74 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Aprašymas

Uni-T UT315A Vibration Tester

The Uni-T UT315A vibration tester is a compact device for rapid diagnostics of rotating and reciprocating machinery, measuring acceleration (0–199.9 m/s²), vibration velocity (0–19.99 cm/s RMS), and displacement (1–1.999 mm P-P). A wide frequency range (up to 10 kHz for acceleration) and good accuracy allow for a realistic assessment of equipment condition and the detection of abnormalities at an early stage. The device offers practical features for daily use, such as result hold, auto-off, and low-battery warning, and operates for over 8 hours on a single 9V battery. It is a tool that works well in both service and maintenance applications.

Included in the set

- Uni-T UT315A vibration tester
- 9V battery (6F22)
- Storage case
- User manual
- Manufacturer's packaging

Manufacturer	Uni-T
Model	UT315A
Acceleration measurement	0 ~ 199.9 m/s ²
Frequency range (acceleration)	10 Hz ~ 10 kHz
Accuracy (acceleration)	±(5% + 0.2 m/s ²)
Velocity measurement	0 ~ 19.99 cm/s (RMS)

Frequency range (velocity)	10 Hz ~ 1 kHz
Accuracy (velocity)	±(5% + 0.02 cm/s)
Displacement measurement	1 ~ 1.999 mm (P-P)
Frequency range (displacement)	10 Hz ~ 500 Hz
Accuracy (displacement)	±(5% + 0.002 mm)
Display	2000 counts
Functions	Data Hold, auto power off, low battery indicator
Power supply	9V battery (6F22)
Weight	395 g
Dimensions	166 × 80 × 30 mm
Certifications	CE, UKCA

GPSR Link: https://psr-assets.innpro.pl/tools/sg_tools_measuring_tools.pdf, Gross weight: 1150, Net weight: 395, Box length: 29,00, Box width: 23,50, Box height: 11,50

Techninė specifikacija

Specifications

Sandėlio grupė Tools/Measuring tools [+119][-130]

Matmenys ir svoris

Matmenys (l × P × A) 29,00cm × 23,00cm × 11,00cm

Svoris 1,15kg