

# Uni-T UT303A+ Infrared Thermometer

Gamintojas: **UNI-T** · Modelis: **UT303A+** · EAN: **6935750530382** · Prekės kodas: **759196**



## 110,90 €

Kaina su PVM

Be PVM: **91,65 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Aprašymas

### Uni-T UT303A+ Infrared Thermometer

The Uni-T UT303A+ infrared thermometer is a functional and user-friendly device for non-contact surface temperature measurement in the range of -32°C to 800°C, offering a fast response time of 250 ms and high accuracy of  $\pm 1.5^{\circ}\text{C}$  or  $\pm 1.5\%$  for temperatures  $\geq 0^{\circ}\text{C}$ , while for negative temperatures, the error is determined by the formula  $\pm(1.5^{\circ}\text{C} + 0.1^{\circ}\text{C}/^{\circ}\text{C})$ . The model is equipped with a single laser pointer for easy targeting, adjustable emissivity (0.1–1.0), and a clear backlit display, allowing for convenient reading of results in various operating conditions.

### Practical functionality for everyday use

The Uni-T UT303A+ offers basic yet extremely useful measurement functions, such as MAX / MIN / AVG / DIFF and HOLD, which enable quick analysis of results. Thanks to a D:S ratio of 30:1, it is possible to take accurate measurements from a greater distance without needing to touch the object being tested. Ergonomic design, intuitive operation, and a rugged housing resistant to drops from heights of up to 1 meter make the device well-suited for everyday use.

### Included in the set

- Uni-T UT303A+ infrared thermometer
- 9V battery
- Carrying case
- User manual
- Blister packaging
- Manufacturer's packaging

**Manufacturer**

Uni-T

|                               |                               |
|-------------------------------|-------------------------------|
| Model                         | UT303A+                       |
| Temperature measurement range | -32°C ~ 800°C                 |
| Repeatability                 | 0.7°C or 0.7%                 |
| D:S ratio                     | 30:1                          |
| Response time                 | 250 ms                        |
| Emissivity adjustment         | 0.1 – 1.0                     |
| Spectral range                | 8–14 μm                       |
| Laser                         | single                        |
| Measurement modes             | MAX / MIN / AVG / DIFF / HOLD |
| Measurement memory            | none                          |
| Alarms                        | visual + audible              |
| Operating temperature         | 0°C ~ 50°C                    |
| Storage temperature           | -20°C ~ 60°C                  |
| Operating humidity            | <90% RH (non-condensing)      |
| Drop test                     | 1 m                           |
| Power supply                  | 9V battery                    |
| Weight                        | 310 g                         |
| Dimensions                    | 172 x 113.5 x 53 mm           |
| Tripod mount                  | Yes                           |

GPSR Link: [https://psr-assets.innpro.pl/tools/sg\\_tools\\_measuring\\_tools.pdf](https://psr-assets.innpro.pl/tools/sg_tools_measuring_tools.pdf), Gross weight: 470, Net weight: 310, Box length: 20,50, Box width: 14,50, Box height: 9,00

## Techninė specifikacija

|                      |                                    |
|----------------------|------------------------------------|
| Specifications       |                                    |
| Sandėlio grupė       | Tools/Measuring tools [+119][-130] |
| Matmenys ir svoris   |                                    |
| Matmenys (l × P × A) | 20,00cm × 14,00cm × 9,00cm         |
| Svoris               | 0,47kg                             |