

Digital Clamp Meter Habotest HT208D

Gamintojas: **HABOTEST** · Modelis: **HT208D** · EAN: **5907489607711** · Prekės kodas: **760516**



56,89 €

Kaina su PVM

Be PVM: **47,02 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Habotest HT208D digital clamp meter

HT208D is a practical device with which you can check the value of various parameters, for example, AC and DC voltage and current, resistance, temperature, inrush current and many others. The product provides accurate measurements, and the results are displayed on the LCD screen. The HT208D also features a flashlight for convenient operation in dark rooms.

Multifunctional device

You will use the HT208D in many situations. You can check the value of AC voltage, resistance, capacitance, temperature, frequency, NCV, etc. Furthermore, you can also check continuity and true RMS value.

Safe use

The device is completely safe to use. You can, for example, detect voltage without touching, thanks to the NCV sensors. The meter's jaws, thanks to their maximum width of 40 mm, allow you to make measurements comfortably without damaging the circuit. The flashlight function ensures comfortable and safe work in dark rooms.

Additional features

When it receives an electromagnetic signal, the NCV sensor will send an audible alarm, and if the voltage or current is high, the LCD screen color will turn orange. What's more, the device will automatically turn off to save power if no action is performed within 15 min.

Function	HT208A	HT208D
DC voltage	6V/60V/600V/1000V ±(1%+3)	6V/60V/600V/1000V ±(1%+3)
AC voltage	6V/60V/600V/750V ±(1.2%+3)	6V/60V/600V/750V ±(1.2%+3)
DC current	n/a	60A/600A/1000A ±(2.5%+5)
AC current	60A/600A/1000A ±(3.0%+5)	60A/600A/1000A ±(3.0%+5)
Resistance	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ ±(1.0%+3)	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ ±(1.0%+3)
Capacity	10nF/100nF/1μF/10μF/100μF/1mF/10mF ±(4.0%+3), 100mF ±(5.0%+5)	10nF/100nF/1μF/10μF/100μF/1mF/10mF ±(4.0%+3), 100mF ±(5.0%+5)
Frequency	10Hz/100Hz/1kHz/10kHz/100kHz/1MHz/10MHz ±(1.0%+3)	10Hz/100Hz/1kHz/10kHz/100kHz/1MHz/10MHz ±(1.0%+3)
Duty	1%~99% ±(1.0%+2)	1%~99% ±(1.0%+2)
Temperature	-40°C~1000°C ±(1.0%+3)	-40°C~1000°C ±(1.0%+3)
Counts	6000	6000
Auto/manual range	Yes	Yes
Continuity	Yes, LED and buzz	Yes, LED and buzz
Diode	Yes	Yes
Data hold	Yes	Yes
NCV	Yes, LED and buzz	Yes, LED and buzz
Double color backlight	Yes	Yes
Flashlight	Yes	Yes
Low battery indicator	Yes	Yes
Auto power off	Yes	Yes
True RMS	Yes	Yes
LPF	Yes	Yes
MAX/MIN	Yes	Yes
V-LoZ	No	Yes

Power	2x AA batteries (in the box)	2x AA batteries (in the box)
Weight	about 380 g	about 380 g
Size	240 x 85 x 40 mm	240 x 85 x 40 mm
Size of jaws	44 mm	44 mm
Safety	EN61010-1, -2-030 EN61010-2-033, EN61326-1 CAT III 1000V, CATIV 600V	EN61010-1, -2-030 EN61010-2-033, EN61326-1 CAT III 1000V, CATIV 600V

Net weight: 649, Box length: 28,50, Box width: 14,00, Box height: 6,00, Gross weight: 670, GPSR Link: https://psr-assets.innpro.pl/tools/sg_tools_measuring_tools.pdf, PPWR: <https://ppwr.innpro.pl/habotest>

Techninė specifikacija

Specifications

Sandėlio grupė

Tools/Measuring tools [+119][-130]

Matmenys ir svoris

Matmenys (l × P × A)

28,00cm × 14,00cm × 6,00cm

Svoris

0,67kg