

DELL PowerEdge T160 server 480 GB Tower (3U) Intel Xeon 6 6315P 2.8 GHz 16 GB DDR5-SDRAM 300 W

Gamintojas: **DELL** · Modelis: **EMEA_PROMO_T160_SPL2** · EAN: **5902002357968** · Prekės kodas: **761285**



2 885,90 €

Kaina su PVM

Be PVM: **2 385,04 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Intel Xeon 6 6315P 2.8 GHz
- ✓ 480 GB
- ✓ 16 GB DDR5-SDRAM
- ✓ Tower (3U) 300 W



Aprašymas

DELL PowerEdge T160. Prozessorfamilie: Intel Xeon 6, Prozessor-Taktfrequenz: 2,8 GHz, Prozessor: 6315P. Speicherkapazität: 16 GB, Interner Speichertyp: DDR5-SDRAM. Gesamtspeicherkapazität: 480 GB. Ethernet/LAN, Verkabelungstechnologie: 10/100/1000Base-T(X). Stromversorgung: 300 W. Gehäusetype: Tower (3U)

Techninė specifikacija

Specifications

Sandėlio grupė

PC-Systeme [+1193][-119]

Processor

Processor family	Intel Xeon 6
Processor manufacturer	Intel
Processor model	6315P
Processor frequency	2.8 GHz
Processor boost frequency	5.2 GHz
Performance cores	4
Processor cores	4
Processor cache	12 MB
Number of processors installed	1
Thermal Design Power (TDP)	55 W
Processor threads	4
Memory types supported by processor	DDR5-SDRAM
Memory clock speeds supported by processor	4800 MHz
Memory	
Internal memory	16 GB
Internal memory type	DDR5-SDRAM
Maximum internal memory	128 GB
Memory slots	4x DIMM
ECC	Yes
Storage	
Total storage capacity	480 GB
RAID support	No
Optical drive type	No
Number of SSDs installed	1
SSD capacity	480 GB
SSD interface	SATA III
SSD size	2.5"
Supported SSD sizes	2.5", 3.5"
Number of SSDs supported	5
Drive writes per day (DWPD)	3
Storage drive adapter included	Yes
Storage drive adapter type	2.5" - 3.5"
Network	
Ethernet LAN	Yes
Cabling technology	10/100/1000Base-T(X)

Ethernet interface type	Gigabit Ethernet
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
USB 2.0 ports quantity	3
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4
VGA (D-Sub) ports quantity	1
Serial ports quantity	1
Design	
Chassis type	Tower (3U)
Product colour	Grey
Software	
Operating system installed	No
Power	
Redundant power supply (RPS) support	No
Power supply	300 W
Number of main power supplies	1
Operational conditions	
Storage temperature (T-T)	-40 - 65 °C
Storage relative humidity (H-H)	5 - 95%
Operating altitude	0 - 3048 m
Non-operating altitude	0 - 12000 m
Carbon footprint	
Total carbon footprint (kg of CO2e)	1182
Total carbon emissions, standard deviation (kg of CO2e)	924
Carbon emissions, manufacturing (kg of CO2e)	319.14
Carbon emissions, logistics (kg of CO2e)	130.02
Carbon emissions, energy usage (kg of CO2e)	709.2
Carbon emissions, end-of-life (kg of CO2e)	23.64
Weight & dimensions	
Width	132.5 mm
Height	332.5 mm
Other features	
Data transfer rate	6 Gbit/s
Bytes per sector	512e

Target workload

Read Intensive (RI)

Matmenys ir svoris

Matmenys (I × P × A)

54,00cm × 48,00cm × 32,00cm

Svoris

11,08kg