

Zebra LI3608 Handheld bar code reader 1D Black, Green

Gamintojas: **ZEBRA** · Modelis: **LI3608-ER20003VZWW** · EAN: **8596375060548** · Prekės kodas: **761598**



525,90 €

Kaina su PVM

Be PVM: **434,63 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Handheld bar code reader Black, Green
- ✓ Scanner type: 1D
- ✓ Codabar, Code 11, Code 128, Code 39, Code 93, GS1 DataBar Expanded, GS1 DataBar Omnidirectional, MSI, Plessey, U.P.C.
- ✓ Working distance: 17.1 m
- ✓ Wired Standard interfaces: RS-232, USB, Keyboard wedge
- ✓ Power source type: DC



Aprašymas

Unstoppable performance for extended-range 1D barcode capture

"As a member of the Zebra 3600 Ultra-Rugged Series of scanners, the practically indestructible 1D/2D DS3608-ER corded and DS3678-ER cordless scanners are ready for one of the world's toughest environments — the warehouse." Designed to capture virtually any 1D barcode from as close as 2 in./5,1 cm to as far as 56 ft./17,1 m away, these scanners provide the ultimate in versatility — workers can capture codes in hand as well as on the top of your warehouse racks. And these scanners are loaded with features that deliver truly unstoppable performance, redefining reliability and management simplicity to drive throughput, accuracy and customer service to a new level.

In addition to superior scanning performance, an ultra-rugged design and unparalleled manageability, you get more features that make this scanner easier than ever for your workers to use, including the crispest aiming pattern for first-time accurate capture of barcodes on pick lists; mix-and-match feedback modes so workers can see, hear or feel successful scans; an extreme temperature rating for freezer use and more. And Zebra's Network Connect for Automation delivers a seamless connection between LI3608-ER/LI3678-ER scanners and your Industrial Ethernet network

without additional third party equipment, reducing complexity, and eliminating a point of failure.

Techninė specifikacija

Specifications	
Sandėlio grupė	Scanner Barcoder [+289][-22]
Scanning	
Type	Handheld bar code reader
Scanner type	1D
Linear (1D) barcodes supported	Codabar, Code 11, Code 128, Code 39, Code 93, GS1 DataBar Expanded, GS1 DataBar Omnidirectional, MSI, Plessey, U.P.C.
2D (matrix & stacked) barcodes supported	Not supported
Working distance	17.1 m
Light levels (direct sunlight)	0 - 108000 lx
Wavelength	660 nm
Pitch reading angle	-65 - 65°
Ports & interfaces	
Connectivity technology	Wired
Standard interfaces	RS-232, USB, Keyboard wedge
Data transfer rate	3 Mbit/s
Performance	
Product colour	Black, Green
International Protection (IP) code	IP65, IP67
Protection features	Dust resistant, Water resistant
LED indicators	Yes
Programming function	Yes
Power	
Power source type	DC
Number of reads per charge	100000
Input voltage	4.5 - 12.6 V
Weight & dimensions	
Weight	327 g
Width	77 mm
Depth	132 mm
Height	185 mm

Operational conditions	
Operating temperature (T-T)	-30 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 95%
Technical details	
Compliance certificates	RoHS
Logistics data	
Harmonized System (HS) code	84716070